

ELKAY®

SPECIFICATIONS

EZH2O® Bottle Filling Station In-Wall Recessed Models EZWS(M)8PK & EZWS(M)DPK

PRODUCT SPECIFICATION

RATED FOR INDOOR USE ONLY


In-wall recessed bottle filling station for use with EDFPBM SwirlFlo® fountains. EZWS(M)8PK shall deliver 8 GPH of 50°F drinking water at 90°F ambient and 80°F inlet water. EZWS(M)DPK shall deliver non-chilled drinking water. Units shall be stainless steel construction with plastic ABS alcove. Sensor-activation with an auto 20-second shut-off timer. Shall include Green Ticker™ displaying count of plastic bottles saved from waste. Bottle filler shall provide 1.1-1.5 gpm flow rate with laminar flow to minimize splashing. Shall include the WaterSentry® Plus 3000-gallon capacity filter, certified to NSF/ANSI 42 and 53, with visual monitor to indicate when replacement is necessary. Shall include integrated silver ion anti-microbial protection in key areas. Unit shall meet ADA guidelines. Unit shall be leadfree design which is certified to NSF/ANSI 61 and 372 and meets Federal and State low-lead requirements. Unit shall be certified to UL399 and CAN/CSA 22.2 No. 120.

STANDARD FEATURES


- Special panel height designed to pair with non-refrigerated EDFPBM SwirlFlo® models
- Sanitary, touchless activation with auto 20-second shut-off (Bottle Filler)
- Integrated Silver Ion Anti-microbial Protection in key areas
- Quick Fill Rate: 1.1 gpm (EZWS(M)8P); 1.5 gpm (EZWS(M)DP)
- Laminar Flow provides minimal splash
- Real Drain System eliminates standing water
- Visual User Interface display includes:
 - Innovative Green Ticker™ counts bottles saved from waste
- Includes lower hinged panel for easy access and servicing

COOLING SYSTEM (Model EZWS(M)8P)

- Compressor: hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with stainless steel tank. Fully insulated with EPS foam which meets UL requirements for self-extinguishing material.
- Refrigerant Control: Refrigerant R134a is controlled by accurately calibrated capillary tube.
- Temperature Control: Enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude requirements. Easily accessible by removing lower grille panel.



Model
EZWS(M)8PK







Model
EZWS(M)DPK



CONSTRUCTION

- Stainless steel bottle filler construction with ABS plastic alcove
- Includes stainless steel lower panel. EZWS(M)8P models have louvered ventilating grille; EZWS(M)DP models have solid panel
- Furnished with MFWS100 wall mounting box constructed of galvanized steel. Mounting can be ordered separately for pre-install.

Warranty: 5 year limited warranty on the unit's refrigeration system. Electrical components and water system are warranted for 12 months from date of installation or 18 months from factory shipment, whichever date falls first.

CAPACITIES CHART									
Model	Voltage / Hertz	Chilling** Capacity	F.L. Amps	Rated Watts	Approx. Ship Wt.	ADA Compliant	UL399 and CAN/CSA 22.2 No. 120 Certified	ANSI/NSF 61 and 372 Certified	GreenSpec® Listed
EZWS(M)8PK	115V / 60 Hz	8 GPH	5.0	370	76	•	•	•	•
EZWS(M)82PK	220V / 50Hz	6.7 GPH	2.5	370	76	•	•	•	•
EZWS(M)83PK	220V / 60Hz	8 GPH	2.5	370	76	•	•	•	•
EZWS(M)DPK	115V / 60 Hz	-	1.0	15	31	•	•	•	•
EZWS(M)DJOPK	220V / 50-60Hz	-	0.5	15	31	•	•	•	•

**Based on 80°F inlet water & 90°F ambient air temp for 50°F chilled drinking water

This specification describes an Elkay product with design, quality and functional benefits to the user. When making a comparison of other producer's offerings, be certain these features are not overlooked.

In keeping with our policy of continuing product improvement, Elkay reserves the right to change specification without notice. Please visit elkay.com for the most current version.

2222 Camden Court
Oak Brook, IL 60523
630-572-3192
elkay.com

© 2014 Elkay
SPEC14-63 (12/2014)