

**KITTELSON
& ASSOCIATES**

1001 SW EMKAY DRIVE, #140
BEND, OR 97702
P 541.312.8300

						KJH
		Addendum # 2				ADDITIONAL
					REVISION	
					DATE	

Submission Date:
06/15/2021

Drawn: BSC	Designed: KJH	Checked: AMR
---------------	------------------	-----------------


PROJECT NO.
25616

Roadway Improvements Campus Drive at Dan O'Brien Way



TYPICAL SECTIONS

SHEET NO.
BA06

11 OF 63



Plot Stamp: 7/12/2021 12:44:40 PM - Ly Nguyen
File: H:\25\25427 - Campus_Daggett Roundabout\Design\CD\CD-Plan & Profile-25616.dwg




Campus Drive Profile
Horz: 1"=20', Vert: 1"=4'

(XX.XX) = Extg. Grade @ CL
XX.XX = Proposed Grade @ CL

CONSTRUCTION NOTES

- 1 Sawcut & Remove Extg. Pavement, Curb & Gutter, & Sidewalk
- 2 City Standard Catch Basin, 4-105
- 3 Sta. "Campus" 107+50 23' LT to Sta. "DOB" 11+50, 23' RT City Standard Type A Curb, 8-100
- 4 Adjust City Standard Manhole to Grade
- 5 Sta. "DOB" 11+55, 19' LT to Sta. "DOB" 17+61, 26' LT City Standard Type A Curb, 8-100
- 6 Sta. "Campus" 107+50, 20' RT to Sta. "DOB" 16+05, 28' RT City Standard Type A Curb, 8-100
- 7 Colored Concrete Pavement, Scored 2'x3', Colored Davis Concrete Color Southern Blush.
- 8 City Standard Type B Curb, 8-105
- 9 City Standard Type C Curb, 8-110, with Reverse Slope Gutter
- 10 City Standard PCC Sidewalk, 8-209
- 11 Landscaping per Landscaping Plan (See Sheet FA03)
- 12 Concrete Median Pavement Mowing Strip, Scored 2'x3', Colored Davis Concrete Color Southern Blush
- 13 Truck Apron, Colored Davis Concrete Color Southern Blush
- 14 Concrete Pedestrian Landing ODOT Standard Detail RD710
- 15 Public Sidewalk Curb Ramp, 8-155
- 16 PCC Driveway Across Sidewalk, 8-210
- 17 Parking Lot Access Driveway, Asphalt
- 18 Concrete Island
- 19 6-inch diameter Schedule 40 PVD Sleeve with Pullstring
- 20 Adjust City Sanitary Manhole to Grade. Relocate Solar Power Pole and Construct Pole Base behind sidewalk at Station 14+75 Left. Top of pole base foundation shall be at grade or buried as required to accommodate electrical gear conduit runs. Electrical work shall be performed by a licensed electrical contractor. Contractor shall relocate vehicle protection bollards. Coordinate work with Engineer, City Inspector, and Ryan Badker at City of Klamath Falls Wastewater Department.
- 21 Remove Existing Catch Basin
- 22 City Pollution Control Manhole with Tee Overflow, 4-140
- 23 Topsoil per Landscaping Plan (See Sheet FA03)

SITE CONSTRUCTION PERMIT SET
City Engineering Division



KITTELSON & ASSOCIATES
1001 SW EMKAY DRIVE, #140
BEND, OR 97702
P 541.312.8300

#	DATE	REVISION	APPD	K/H
1	7/8/2021	Addendum #2		



Submission Date:
06/15/2021
Drawn: BSC
Designed: XXX
Checked: AMR

PROJECT NO.
25616

Roadway Improvements
Campus Drive at Dan O'Brien Way
CONSTRUCTION PLAN & NOTES



SHEET NO.
C01
21 OF 63

Plot Stamp: 7/12/2021 12:49:02 PM - Ly Nguyen
File: H:\25\25427 - Campus_Daggett Roundabout\Design\CD\CD-Plan & Profile-25616.dwg



Dan O'Brien Way Profile
Horz: 1"=20', Vert: 1"=4'

(XX.XX) = Extg. Grade @ CL
XX.XX = Proposed Grade @ CL



CONSTRUCTION NOTES

- 1 Sawcut & Remove Extg. Pavement, Curb & Gutter, & Sidewalk
- 2 City Standard Catch Basin, 4-105
- 3 Protect Existing Curb, Curb & Gutter.
- 4 6-inch diameter Schedule 40 PVD Sleeve with Pullstring
- 5 Not Used
- 6 Sta. "DOB" 11+55, 19' LT to
Sta. "DOB" 17+61, 26' LT
City Standard Type A Curb, 8-100
- 7 Sta. "Campus" 107+50, 20' RT to
Sta. "DOB" 16+05, 28' RT
City Standard Type A Curb, 8-100
- 8 City Standard Type B Curb, 8-105
- 9 City Standard PCC Sidewalk, 8-209
- 10 Concrete Pedestrian Landing
ODOT Standard Detail RD710
- 11 Public Sidewalk Curb Ramp, 8-155
- 12 PCC Driveway Across Sidewalk, 8-210
- 13 Concrete Island
- 14 End Type A Curb, Match Existing
- 15 Remove Existing Catch Basin
- 16 City Pollution Control Manhole with Tee Overflow, 4-140
- 17 Adjust Sanitary Manhole to Grade
- 18 Adjust Rim to Grade, Minor Adjustment
- 19 Protect Existing Catch Basin
- 20 End Type B Curb
Sta. "DOB" 16+57, 5' RT to
Sta. "DOB" 16+71, 6' RT
City Standard Type A Curb, 8-100
- 21
- 22 Sta. "DOB" 16+57, 4' LT to
Sta. "DOB" 16+71, 3.5' LT
City Standard Type A Curb, 8-100



**KITTELSON
& ASSOCIATES**

1001 SW EMKAY DRIVE, #140
BEND, OR 97702
P 541.312.8300

#	DATE	REVISION	APP'D	K/H
1	7/8/2021	Addendum #2		

Submission Date:
06/15/2021
Drawn: BSC
Designed: XXX
Checked: AMR

PROJECT NO.
25616

Roadway Improvements
Campus Drive at Dan O'Brien Way

CONSTRUCTION PLAN & NOTES

SHEET NO.
C04
24 OF 63

1. Include a list all personnel (by name and position) that are responsible for the design, installation and maintenance of stormwater measures (e.g. ESCP developer, BMP installer (see Section 4.10), as well as their individual responsibilities. (Section 4.4 c.ii)
2. Visual monitoring inspection reports must be made in accordance with DEQ 1200-C permit requirements. (Section 6.5)
3. Inspection logs must be kept in accordance with DEQ's 1200-C permit requirements. (Sections 6.5g)
4. Retain a copy of the ESCP and all revisions on site and make it available on request to DEQ, Agent, or the local municipality. (Section 4.7)
5. The permit registrant must implement the ESCP. Failure to implement any of the control measures or practices described in the ESCP is a violation of the permit. (Sections 4 and 4.11)
6. The ESCP must be accurate and reflect site conditions. (Section 4.8)
7. Submission of all ESCP revisions is not required. Submittal of the ESCP revisions is only under specific conditions. Submit all necessary revision to DEQ or Agent within 10 days. (Section 4.9)
8. Sequence clearing and grading to the maximum extent practical to prevent exposed inactive areas from becoming a source of erosion. (Section 2.2.2)
9. Create smooth surfaces between soil surface and erosion and sediment controls to prevent stormwater from bypassing controls and ponding. (section 2.2.3)
10. Identify, mark, and protect (by construction fencing or other means) critical riparian areas and vegetation including important trees and associated rooting zones, and vegetation areas to be preserved. Identify vegetation buffer zones between the site and sensitive areas (e.g., wetlands), and other areas to be preserved, especially in perimeter areas. (Section 2.2.1)
11. Preserve existing vegetation when practical and re-vegetate open areas. Re-vegetate open areas when practicable before and after grading or construction. Identify the type of vegetative seed mix used. (Section 2.2.5)
12. Maintain and delineate any existing natural buffer within the 50-feet of waters of the state. (Section 2.2.4)
13. Install perimeter sediment control, including storm drain inlet protection as well as all sediment basins, traps, and barriers prior to land disturbance. (Sections 2.1.3)
14. Control both peak flow rates and total stormwater volume, to minimize erosion at outlets and downstream channels and streambanks. (Sections 2.1.1 and 2.2.16)
15. Control sediment as needed along the site perimeter and at all operational internal storm drain inlets at all times during construction, both internally and at the site boundary. (Sections 2.2.6 and 2.2.13)
16. Establish concrete truck and other concrete equipment washout areas before beginning concrete work. (Section 2.2.14)
17. Apply temporary and/or permanent soil stabilization measures immediately on all disturbed areas as grading progresses. Temporary or permanent stabilizations measures are not required for areas that are intended to be left unvegetated, such as dirt access roads or utility pole pads. (Sections 2.2.20 and 2.2.21)
18. Establish material and waste storage areas, and other non-stormwater controls. (Section 2.3.7)
19. Keep waste container lids closed when not in use and close lids at the end of the business day for those containers that are actively used throughout the day. For waste containers that do not have lids, provide either (1) cover (e.g., a tarp, plastic sheeting, temporary roof) to prevent exposure to wastes to precipitation, or (2) a similarly effective means designed to prevent the discharge to pollutants (e.g., secondary containment). (Section 2.3.7)
20. Prevent tracking of sediment onto public or private roads using BMPs such as: construction entrance, graveled (or paved) exits and parking areas, gravel all unpaved roads located onsite, or use an exit tire wash. These BMPs must be in place prior to land-disturbing activities. (Section 2.2.7)
21. When trucking saturated soils from the site, either use water-tight trucks or drain loads on site. (Section 2.2.7.f)
22. Control prohibited discharges from leaving the construction site, i.e., concrete wash-out, wastewater from cleanout of stucco, paint and curing compounds. (Section 1.5 and 2.3.9)
23. Ensure that steep slope areas where construction activities are not occurring are not disturbed. (Section 2.2.10)
24. Prevent soil compaction in areas where post-construction infiltration facilities are to be installed. (Section 2.2.12)
25. Use BMPs to prevent or minimize stormwater exposure to pollutants from spills; vehicles and equipment fueling, maintenance, and storage; other cleaning and maintenance activities; and waste handling activities. These pollutants include fuel, hydraulic fluid, and other oils from vehicles and machinery, as well as debris, fertilizer, and pesticides and herbicides, paints, solvents, curing compounds and adhesive from construction operations. (Section 2.2.15 and 2.3)
26. Provide plans for sedimentation basins that have been designed per Section 2.2.17 and stamped by an Oregon Professional Engineer. (See Section 2.2.17.a)
27. If engineered soils are used on site, a sedimentation basin/impoundment must be installed. (see Sections 2.2.17 and 2.2.18)
28. Provide a dewatering plan for accumulated water from precipitation and uncontaminated groundwater seepage due to shallow excavation activities. (See Section 2.4)
29. Implement the following BMPs when applicable: written spill prevention and response procedures, employee training on spill prevention and proper disposal procedures, spill kits in all vehicles, regular maintenance schedule for vehicles and machinery, material delivery and storage controls, training and signage, and covered storage areas for waste and supplies. (Section 2.3)
30. Use water, soil-binding agent or other dust control technique as needed to avoid wind-blown soil. (Section 2.2.9)
31. The application rate for fertilizers used to reestablish vegetation must follow manufacturer's recommendations to minimize nutrient releases to surface waters. Exercise caution when using time-release fertilizers within any waterway riparian zone. (Section 2.3.5)
32. If an active treatment system (for example, electro-coagulation, flocculation, filtration, etc.) for sediment or other pollutant removal is employed, submit an operation and maintenance plan (including system schematic, location frequency) before operating the treatment system. Obtain Environmental Management Plan approval from DEQ before operating the treatment system. Operate and maintain the treatment system according to manufacturer's specifications. (Section 1.2.9)
33. Temporarily stabilize soils at the end of the shift before holidays and weekends, if needed. The registrant is responsible for ensuring that soils are stable during rain events at all times of the year. (Section 2.2)
34. As needed based on weather conditions, at the end of each workday soil stockpiles must be stabilized or covered, or other BMPs must be implemented to prevent discharges to surface waters or conveyance systems leading to surface waters. (Section 2.2.8)
35. Sediment fence: remove trapped sediment before it reaches one third of the above ground fence height and before fence removal. (Section 2.1.5.b)
36. Other sediment barriers (such as biobags): remove sediment before it reaches two inches depth above ground height and before BMP removal. (Section 2.1.5.c)
37. Catch basins: clean before retention capacity has been reduced by fifty percent. Sediment basins and sediment traps: remove trapped sediments before design capacity has been reduced by fifty percent and at completion of project. (Section 2.1.5.d)
38. Within 24 hours, significant sediment that has left the construction site, must be remediated. Investigate the cause of the sediment release and implement steps to prevent a recurrence of the discharge within the same 24 hours. Any in-stream clean-up of sediment shall be performed according to the Oregon Department of State Lands required timeframe. (Section 2.2.19.a)
39. The intentional washing of sediment into storm sewers or drainage ways must not occur. Vacuuming or dry sweeping and material pickup must be used to cleanup released sediments. (Section 2.2.19)
40. Document any portion(s) of the site where land disturbing activities have permanently ceased or will be temporarily inactive for 14 or more calendar days. (Section 6.5.f)
41. Provide temporary stabilization for that portion of the site where construction activities cease for 14 days or more with a covering of blown straw and a tackifier, loose straw, or an adequate covering of compost mulch until work resumes on that portion of the site. (Section 2.2.20)
42. Do not remove temporary sediment control practices until permanent vegetation or other cover of exposed areas is established. Once construction is complete and the site is stabilized, all temporary erosion controls and retained soils must be removed and disposed of properly, unless needed for long term use following termination of permit coverage. (Section 2.2.21)

1. Implementation of the grading and erosion control plan and the construction, maintenance, replacement and upgrading of erosion control facilities is the responsibility of the applicant/owner and their contractor/subcontractors until all construction is completed and approved, and permanent cover is established on the site. Grading and erosion control shall comply with the construction documents and City standards.
2. The stabilized construction entrance shall be installed prior to the beginning of construction and maintained for the duration of the project. It shall be sole entrance or egress from the site. Additional measures may be required to ensure that all paved areas are kept clean for the duration of the project.
3. The boundaries of the clearing limits shown on this plan shall be clearly flagged in the field prior to construction. During the construction period, no disturbance beyond the flagged clearing limits shall be permitted. The flagging shall be maintained by the applicant/owner and their contractors/subcontractors for the duration of construction.
4. Erosion control measures shown on this plan must be constructed in conjunction with all clearing and grading activities, and in such a manner as to ensure that sediment and sediment laden water do not leave the site.
5. The erosion control facilities shown on this plan are the minimum requirements for anticipated site conditions. During the construction period, these erosion control facilities shall be upgraded as needed for unexpected storm events or site condition and to ensure that sediment and sediment laden water do not leave the site.
6. Erosion control facilities shall be inspected and maintained a minimum of once per month and within 24 hours following a storm event.
7. Visible deposits of sediment that leave the site shall be cleaned up within 24 hours and placed back onto the site or properly disposed. Under no condition shall sediment from the construction site be washed into sewers, drainage courses, or other portions of the conveyance system.
8. Excess soil from the site shall be hauled to the site specified on the erosion control plan. A separate permit is required for the fill site if the quantity hauled exceeds 50 cubic yards.
9. At no time shall more than one foot of sediment be allowed to accumulate within a trapped catch basin. All catch basins and conveyance systems shall be cleaned prior to paving. The cleaning operation shall not flush sediment laden water into the downstream system.
10. Dust Control: Preventative measures to minimize wind transport of soil shall be implemented when a nuisance or traffic hazard may be created or when sediment transported by wind may be deposited in water resources.
11. Once construction is complete and permanent cover is established, call for final inspection from the City. Remove temporary erosion control measures when approved by the City.
12. At the time of project close-out, for those requiring a DEQ 1200-C permit, the City will not accept the project until DEQ has satisfactorily approved the project and terminated the DEQ permit. In lieu of that requirement the developer will need to apply for a city site construction permit for grading purposes only. An updated plan and current fee will apply and be submitted with the permit application. The city permit will remain active until the developer has an approved termination of the 1200-C permit by DEQ, which a copy will be provided to the City.

REFER TO DEQ GUIDANCE MANUAL FOR A COMPREHENSIVE LIST OF AVAILABLE BMP'S

[illegible]

SITE CONSTRUCTION PERMIT SET

City Engineering Division



1001 SW EMKAY DRIVE, #140
BEND, OR 97702
P 541.312.8300

[illegible]

Submission Date: 06/15/2021		
Drawn: BSC	Designed: KJH	Checked: AMR

PROJECT NO.
25616

Roadway Improvements Campus Drive at Dan O'Brien Way

GRADING & EROSION CONTROL NOTES

SHEET NO.
FB01

43 OF 63

PRE-CONSTRUCTION NOTES

All Base Erosion Sediment Control Measures (Inlet Protection, Perimeter Sediment Control, Gravel Construction Entrances, Etc.) Must Be In Place, Functional, And Approved In An Initial Inspection, Prior To Commencement Of Construction Activities.

Sediment Barriers Approved For Use Include Sediment Fence, Berms Constructed Out Of Mulch, Chippings, Or Other Suitable Material, Straw Wattles, Or Other Approved Materials.

Sensitive Resources Including, But Not Limited To, Trees, Wetlands, And Riparian Protection Areas Shall Be Clearly Delineated With Orange Construction Fencing In A Manner That Is Clearly Visible To Anyone In The Area. No Activities Are Permitted To Occur Beyond The Construction Barrier.

Tree Protection Fencing Shall Be 4' Tall Orange Construction Fence, Secured To 6' Tall Metal Posts, Driven 2' Into The Ground.

GENERAL NOTES


All Existing Inlets To Be Removed Shall Be Protected From Sediment Laden Water Until The Inlet Is Removed

Staging To Be Done Within Public ROW Or Approved Alternate

No Stock Piling Within Staging Areas, Without Contractor Supplied Erosion Control Plan

Erosion Control Details to Be Provided at 90% Submittal

Seed All Disturbed Areas With EC Mix Unless Otherwise Noted On Landscape Plans



LEGEND

- XX

XX

XX

XX

Sediment Fence
- ---

Existing ROW Line
- ---

Proposed ROW Line
- ---

Existing Major Contours
- ---

Existing Minor Contours
- ---

Proposed Major Contours
- ---

Proposed Minor Contours
- Flow Arrow
- ⓓ

ⓓ

Extg./Proposed MH
- ■

Extg./Proposed CB
- ⊠

⊠

Inlet Protection
- ⊠

Concrete Washout Facility
- ★

★

Trees to Remain
- ✕

✕

Trees to Removed

CONSTRUCTION NOTES

- 1


Install Inlet Protection.
(For Details, See Sht. FB06)
- 2

Install Sediment Fence.
(For Details, See Sht. FB06)
- 3

Area of Seed Restoration

SITE CONSTRUCTION PERMIT SET

City Engineering Division




Roadway Improvements
Campus Drive at Dan O'Brien Way

GRADING & EROSION CONTROL PLANS

SHEET NO.
FB02

44 OF 63



KITTELSON & ASSOCIATES

1001 SW EMKAY DRIVE, #140
BEND, OR 97702
P 541.312.8300

#	DATE	REVISION	APPD
1	7/8/2021	Addendum #2	KJH

Submission Date:
06/15/2021

Drawn: BSC
Designed: KJH
Checked: AMR

PROJECT NO.
25616

PRE-CONSTRUCTION NOTES

All Base Erosion Sediment Control Measures (Inlet Protection, Perimeter Sediment Control, Gravel Construction Entrances, Etc.) Must Be In Place, Functional, And Approved In An Initial Inspection, Prior To Commencement Of Construction Activities.

Sediment Barriers Approved For Use Include Sediment Fence, Berms Constructed Out Of Mulch, Chippings, Or Other Suitable Material, Straw Wattles, Or Other Approved Materials.

Sensitive Resources Including, But Not Limited To, Trees, Wetlands, And Riparian Protection Areas Shall Be Clearly Delineated With Orange Construction Fencing In A Manner That Is Clearly Visible To Anyone In The Area. No Activities Are Permitted To Occur Beyond The Construction Barrier.

Tree Protection Fencing Shall Be 4' Tall Orange Construction Fence, Secured To 6' Tall Metal Posts, Driven 2' Into The Ground.

GENERAL NOTES


All Existing Inlets To Be Removed Shall Be Protected From Sediment Laden Water Until The Inlet Is Removed

Staging To Be Done Within Public ROW Or Approved Alternate

No Stock Piling Within Staging Areas, Without Contractor Supplied Erosion Control Plan

Erosion Control Details to Be Provided at 90% Submittal

Seed All Disturbed Areas With EC Mix Unless Otherwise Noted On Landscape Plans



LEGEND


- xx xx xx xx Sediment Fence
- Existing ROW Line
- Proposed ROW Line
- 250 Existing Major Contours
- 249 Existing Minor Contours
- 250 Proposed Major Contours
- 249 Proposed Minor Contours
- Flow Arrow
- Extg./Proposed MH
- Extg./Proposed CB
- Inlet Protection
- Concrete Washout Facility
- Trees to Remain
- Trees to Removed


CONSTRUCTION NOTES

- 1 Install Inlet Protection. (For Details, See Sht. FB06)
- 2 Install Sediment Fence. (For Details, See Sht. FB06)
- 3 Area of Seed Restoration

SITE CONSTRUCTION PERMIT SET

City Engineering Division





KITTELSON & ASSOCIATES
1001 SW EMKAY DRIVE, #140
BEND, OR 97702
P 541.312.8300

#	DATE	REVISION	APP'D
1	7/8/2021	Addendum #2	KJH

Submission Date: 06/15/2021

Drawn: BSC Designed: KJH Checked: AMR

PROJECT NO. 25616

Roadway Improvements
Campus Drive at Dan O'Brien Way

GRADING & EROSION CONTROL PLANS

SHEET NO. FB03

45 OF 63

PRE-CONSTRUCTION NOTES

All Base Erosion Sediment Control Measures (Inlet Protection, Perimeter Sediment Control, Gravel Construction Entrances, Etc.) Must Be In Place, Functional, And Approved In An Initial Inspection, Prior To Commencement Of Construction Activities.

Sediment Barriers Approved For Use Include Sediment Fence, Berms Constructed Out Of Mulch, Chippings, Or Other Suitable Material, Straw Wattles, Or Other Approved Materials.

Sensitive Resources Including, But Not Limited To, Trees, Wetlands, And Riparian Protection Areas Shall Be Clearly Delineated With Orange Construction Fencing In A Manner That Is Clearly Visible To Anyone In The Area. No Activities Are Permitted To Occur Beyond The Construction Barrier.

Tree Protection Fencing Shall Be 4' Tall Orange Construction Fence, Secured To 6' Tall Metal Posts, Driven 2' Into The Ground.

GENERAL NOTES


All Existing Inlets To Be Removed Shall Be Protected From Sediment Laden Water Until The Inlet Is Removed

Staging To Be Done Within Public ROW Or Approved Alternate


No Stock Piling Within Staging Areas, Without Contractor Supplied Erosion Control Plan

Erosion Control Details to Be Provided at 90% Submittal

Seed All Disturbed Areas With EC Mix Unless Otherwise Noted
On Landscape Plans



LEGEND






CONSTRUCTION NOTES

- 1 Install Inlet Protection.
(For Details, See Sht. FB06)
- 2 Install Sediment Fence.
(For Details, See Sht. FB06)
- 3 Area of Seed Restoration

SITE CONSTRUCTION PERMIT SET

City Engineering Division



**KITTELSON
& ASSOCIATES**

BEND, OR 97702
P 541.312.8300

[illegible]

Submission Date:
06/15/2021

Drawn: BSC	Designed: KJH	Checked: AMR
---------------	------------------	-----------------

PROJECT NO.
25616

Roadway Improvements Campus Drive at Dan O'Brien Way

2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841

SHEET NO.
FB04

6 OF 63