OREGON MANUFACTURING & INNOVATION CENTER


53207 CHARLES T PARKER WAY, SCAPPOOSE, OR 97056


BUILDING RETROFIT AND SITE UPGRADES

EDA Award Number: No. 07-01-07446









DRAWING LIST

CIVIL DRAWINGS (AKS)

COOO - COVER SHEET WITH SITE & VICINITY MAPS

COO1 - GENERAL CONSTRUCTION NOTES

CO02 - GENERAL CONSTRUCTION NOTES COO3 - EXISTING CONDITIONS PLAN

CO50 - EROSION AND SEDIMENT CONTROL COVER SHEET

CO52 - GRADING, CONSTRUCTION, EROSION AND SEDIMENT CONTROL PLAN CO53 - EROSION AND SEDIMENT CONTROL DETAILS

CO71 - SURCHARGE GRADING PLAN CO72 - SURCHARGE DETAILS

C100 - SITE PLAN

CO70 - GRADING PLAN

C200 - STORMWATER DRAINAGE PLAN

C300 - COMPOSITE UTILITY PLAN

C501 - DETAILS C502 - DETAILS

C503 - DETAILS C504 - DETAILS

L100 - LANDSCAPING PLAN L101 - LANDSCAPING DETAILS

L200 - IRRIGATION PLAN L201 - IRRIGATION DETAILS

ARCHITECTURAL (AKAAN) CS-1 - COVER SHEET

CS-2 - GENERAL NOTES & SPECIFICATIONS FLS-1 - FIRE LIFE SAFETY PLANS OF EAST OFFICE AREA

(FOR ROOM 201 CHANGE OF OCCUPANCY)

A1.3 - SECOND FLOOR PLAN - EAST A1.4 - SECOND FLOOR PLAN - WEST

A1.5 - ATTIC FLOOR PLAN A2.1 - EXTERIOR ELEVATIONS A2.2 - ENLARGED EXTERIOR ELEVATIONS - ENTRIES

A3.1 - BUILDING SECTIONS & DETAILS

A3.2 – EXTERIOR DETAILS A3.3 – EXTERIOR DETAILS

A4.1 - ENLARGED PLANS - ELEVATOR & WHEELCHAIR LIFT, MISC. DETAILS

A4.2 - INTERIOR ELEVATIONS & DETAILS - CORRIDOR, RESTROOMS A4.3 - INTERIOR ELEVATIONS & DETAILS - RECEPTION

A4.4 - DETAILS - RECEPTION A4.5 - FINISH SCHEDULE & FIRST FLOOR FINISH PLAN

A4.6 - SECOND FLOOR FINISH PLAN & CORRIDOR REFLECTED CEILING PLANS

A5.0 - DOOR & HARDWARE SCHEDULES, TYPES & DETAILS A5.1 - WINDOW TYPES & DETAILS

DEFERRED SUBMITTALS:

• FIRE SPRINKLER MODIFICATIONS: CONTRACTOR WILL PROVIDE DRAWINGS AND OTHER INFORMATION AS REQUIRED BY THE OSSC FOR THE MODIFICATIONS TO THE EXISTING SPRINKLER SYSTEM.

• ELEVATOR & ADA LIFT: CONTRACTOR WILL PROVIDE DRAWINGS AND OTHER INFORMATION AS REQUIRED BY THE OSSC FOR THE INSTALLATION OF THE ELEVATOR AND ADA LIFT.

• AIR CURTAIN: CONTRACTOR SHALL PROVIDE SUBMITTALS FOR PROJECT ENGINEER'S AND BUILDING OFFICIAL'S REVIEW OF PROPOSED METHOD OF ATTACHING AIR CURTAIN TO EXISTING STRUCTURE. CONTRACTOR SHALL COORDINATE WITH OVERHEAD DOOR INSTALLER AND OTHER AFFECTED TRADES.

GENERAL SCOPE OF WORK DESCRIPTION:

UNDERGROUND UTILITY CONNECTIONS TO PUBLIC INFRASTRUCTURE INCLUDING CITY WATER, CITY SEWER, GAS, AND FIRE SPRINKLER SYSTEM CONNECTION TO CITY WATER AND MODIFICATIONS TO REMOVE EXISTING FIRE PUMP & FIRE SPRINKLER WATER SUPPLY STORAGE TANKS. CONSTRUCTION OF NEW ACCESS DRIVES, NEW PARKING LOT, PARKING LOT STORM SYSTEM, PARKING LOT LIGHTING, NEW MONUMENT SIGN, AND LANDSCAPING.

REMOVAL OF EXISTING OVERHEAD DOORS, REPLACE SOME WITH NEW DOORS, INFILL OTHERS WITH WALLS AND WINDOWS, MISCELLANEOUS OTHER MODIFICATIONS TO EXTERIOR, INSULATION AND NEW HEATING AND VENTILATION AND NEW LIGHTING FIXTURES TO ENTIRE SHOP FLOOR, (2) NEW OVERHEAD CRANES IN SHOP AREA, INSTALLATION OF ELEVATOR AND ADA LIFT TO UPPER OFFICE AREAS, AND MISCELLANEOUS RELATED RENOVATIONS.

STRUCTURAL DRAWINGS (PSE)

SO.O – GENERAL NOTES S1.0 - SITE PLAN

S1.1 - 2ND FLOOR FRAMING PLAN S1.2 - CEILING FRAMING PLAN

S2.0 - STRUCTURAL DETAILS S2.1 - STRUCTURAL DETAILS S2.2 – STRUCTURAL DETAILS

M/E/P DRAWINGS (FLUENT)

MECHANICAL

MO.00 - LEGEND & SCHEDULES M1.00 - 1ST FLOOR MECHANICAL M1.10 - 2ND FLOOR MECHCANICAL

M1.20 - ATTIC MECHANICAL

PLUMBING PO.00 - PLUMBING LEGEND AND SCHEDULES

P1.00 - 1ST FLOOR PLUMBING P1.10 - 2ND FLOOR PLUMBING P1.20 - DETAIL VIEWS

P2.00 - PLUMBING DETAILS

E0.00 - COVER SHEET & LEGENDS

E1.00 ELECTRICAL SITE PLAN

E312 FIRST FLOOR EAST WING POWER

E422 SECOND FLOOR EAST WING LIGHTING

E612 FIRST FLOOR EAST WING TECHNOLOGY E621 SECOND FLOOR WEST WING TECHNOLOGY

E622 SECOND FLOOR EAST WING TECHNOLOGY

E700 ELECTRICAL DETAILS

Scappoose, Oregon 97056 503-983-0573

> \Box OREGON MANUFACTURININNOVATION CENTER R &

101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3

WILLIAM ALLAN

ST. HELENS, OREGON

PROJECT TEAM:

AKS ENGINEERING & FORESTRY

12965 SW Herman Road, Suite 100

PETERSON STRUCTURAL ENGINEERS

CIVIL ENGINEER:

Tualatin, OR 97062

Portland, OR 97225

MEP ENGINEER:

2110 State Street Salem, Oregon 97301

P. 503-447-5030

OWNER:

P. 503.292.1635

STRUCTURAL ENGINEER

FLUENT ENGINEERING INC

OMIC R&D / OREGON TECH.

27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director

33701 Charles T. Parker Way

Procurement and Contract Services

9400 SW Barnes Road, Suite 100

P: 503.563.6151

F: 503.563.6152

SCALE: DRAWN BY: CHECKED BY: CAD FILE: 1404_A00.DWG

REVISIONS DATE DESCRIPTION

AS NOTED

1 03/23/2020 PER BLDG OFF REQ

CONTENTS:

DATE:

DRAWING LIST, SYMBOLS LOCATION MAP

SHEET NO:

FOR PERMIT



VEHICULAR ACCESS AND PARKING: AS DETERMINED BY PROPERTY OWNER.

PERMITS AND FEES: THE CONTRACTOR SHALL APPLY FOR, OBTAIN, AND PAY FOR PERMITS. CERTIFICATE OF OCCUPANCY, FEES, LICENSES, AND UTILITY COMPANY CHARGES REQUIRED TO PERFORM THE WORK. SUBMIT COPIES TO

CODES: COMPLY WITH ALL APPLICABLE CODES AND REGULATIONS OF AUTHORITIES HAVING JURISDICTION INCLUDING BUT NOT LIMITED TO COLUMBIA COUNTY BUILDING CODES, CITY OF SCAPPOOSE LAND USE AND BUILDING DEPARTMENT, OREGON RESIDENTIAL SPECIALTY CODE, (LATEST EDITION) O.S.H.A. HEALTH AND SAFETY REGULATIONS, POLICE, FIRE DEPARTMENT AND RESCUE SQUAD RULES, D.E.Q. REGULATIONS, LOCAL UTILITY COMPANY RULES, AND THE OREGON UTILITY NOTIFICATION RULES.

DESIGN LOADS: LOADS AND CODE RESTRICTIONS FOR ALL DESIGN CONSIDERATIONS SHALL TO CONFORM TO ALL ORDINANCES AND STATE AND LOCAL BUILDING CODES (LATEST EDITION).

TEST REPORTS AND INSPECTIONS: SUBMIT IN DUPLICATE EACH BUILDING INSPECTORS REPORT, MATERIALS TEST, OR SIMILAR QUALITY-CONTROL SERVICE PERFORMED. SUBMIT COPIES OF INSPECTION REPORTS, NOTICES AND SIMILAR COMMUNICATIONS TO OWNER.

INTENT: DRAWINGS AND SPECIFICATIONS ARE INTENDED TO PROVIDE THE BASIS FOR PROPER COMPLETION OF THE WORK SUITABLE FOR THE INTENDED USE. ANYTHING NOT EXPRESSLY SET FORTH BUT WHICH IS REASONABLY IMPLIED OR NECESSARY FOR PROPER PERFORMANCE OF THE PROJECT SHALL

UNLESS OTHERWISE NOTED PROVIDE THE MANUFACTURER'S RECOMMENDED STANDARD ACCESSORIES, SEAL ANTS, FASTENERS, AND OTHER PRODUCTS FOR PROPER INSTALLATION.

MANUFACTURER'S AND INDUSTRY STANDARDS: INSTALL ALL MATERIALS. MANUFACTURED ITEMS AND EQUIPMENT IN STRICT ACCORDANCE WITH MANUFACTURER'S OR APPLICABLE INDUSTRY AGENCY'S LATEST PUBLISHED RECOMMENDED SPECIFICATIONS OR THOSE REFERENCED HEREIN. IN THE EVENT OF CONFLICT BETWEEN SPECIFICATIONS AND DRAWINGS AND INDUSTRY STANDARDS NOTIFY THE ARCHITECT IN WRITING BEFORE PROCEEDING WITH THE WORK. THE MANUFACTURER'S OR INDUSTRY AGENCY'S SPECIFICATIONS OR RECOMMENDATIONS SHALL GOVERN UNLESS THE ARCHITECT ORDERS IN WRITING A DEVIATION SUBSEQUENT TO SUCH NOTICE.

DELIVERY, STORAGE, AND HANDLING: PROTECT ALL MATERIALS FROM PHYSICAL DAMAGE AND FROM DETERIORATION BY MOISTURE, SOILING, AND OTHER SOURCES. STORE IN A DRY LOCATION AND COMPLY WITH MANUFACTURER'S WRITTEN INSTRUCTIONS FOR HANDLING, STORING, AND PROTECTING DURING AND AFTER INSTALLATION.

EXISTING CONDITIONS: BEFORE DOING ANY WORK THE CONTRACTOR SHALL VERIFY ALL MEASUREMENTS AND CONDITIONS AND NOTIFY ARCHITECT OF EXISTING CONDITIONS DIFFERING FROM THOSE INDICATED ON DRAWINGS. RESULTING ERRORS CAUSED BY THE FAILURE TO EXERCISE SUCH PRECAUTIONS SHALL NOT BE CONSIDERED SUBSEQUENTLY AS A BASIS FOR ADDITIONAL COMPENSATION.

DIMENSIONS: DO NOT SCALE DRAWINGS. VERIFY DIMENSIONS INDICATED ON DRAWINGS WITH FIELD DIMENSIONS, NOTIFY ARCHITECT OF DISCREPANCIES PRIOR TO CONTINUING WORK.

COORDINATION: COORDINATE WITH OTHER TRADES PRIOR TO EACH PHASE OF WORK. VERIFY THAT RELATED CONSTRUCTION HAS BEEN COMPLETED PRIOR TO COMMENCEMENT OF WORK

INSPECT SUBSTRATES AND REPORT UNSATISFACTORY CONDITIONS IN WRITING. DO NOT PROCEED UNTIL UNSATISFACTORY CONDITIONS HAVE BEEN CORRECTED. START OF WORK CONSTITUTES ACCEPTANCE OF EXISTING CONDITIONS AND SUBSTRATES.

PROVIDE OPENINGS, AND REINFORCING AS REQUIRED FOR CHASES, SLEEVES, AND SIMILAR PROVISIONS IN WALLS, PARTITIONS, FLOORS, AND OTHER CONSTRUCTION AS NEEDED.

TAKE FIELD MEASUREMENTS PRIOR TO FABRICATION. FORM TO REQUIRED SHAPES AND SIZES WITH TRUE EDGES, LINES AND ANGLES. PROVIDE INSERTS AND TEMPLATES AS NEEDED FOR WORK OF OTHER TRADES.

INSTALL MATERIALS IN PROPER RELATION WITH ADJACENT CONSTRUCTION AND WITH PROPER APPEARANCE.

RESTORE ITEMS DAMAGED DURING INSTALLATION. REPLACE ITEMS WHICH CANNOT BE RESTORED AT NO ADDITIONAL EXPENSE TO THE OWNER.

CLEAN AND PROVIDE MAINTENANCE ON COMPLETED CONSTRUCTION AS FREQUENTLY AS NECESSARY THROUGH THE REMAINDER OF THE CONSTRUCTION PERIOD. ADJUST AND LUBRICATE OPERABLE COMPONENTS TO ASSURE OPERABILITY WITHOUT DAMAGING EFFECTS.

PROTECT INSTALLED MATERIALS FROM DAMAGE. PROVIDE TEMPORARY COVERINGS OR ENCLOSURES WHERE INSULATION IS SUBJECT TO ABUSE AND CANNOT BE CONCEALED AND PROTECTED BY PERMANENT CONSTRUCTION IMMEDIATELY AFTER INSTALLATION.

MOUNTING HEIGHTS: WHERE MOUNTING HEIGHTS ARE NOT INDICATED, INSTALL INDIVIDUAL COMPONENTS AT STANDARD MOUNTING HEIGHTS RECOGNIZED WITHIN THE INDUSTRY FOR THE PARTICULAR APPLICATION INDICATED. REFER QUESTIONABLE MOUNTING HEIGHT DECISIONS TO THE OWNER FOR FINAL

TEMPORARY TRASH STORAGE AND REMOVAL: CONTRACTOR SHALL MAKE PROVISIONS AND COORDINATE WITH THE OWNER FOR FOR THE STORAGE AND REMOVAL OF ALL CONSTRUCTION DEBRIS AND SHALL PAY FOR ALL ASSOCIATED COSTS.

CONTRACTOR TO PROVIDE ALL TEMPORARY LIGHTING AS REQUIRED.

MANUFACTURER'S S WRITTEN INSTALLATION INSTRUCTIONS.

Generated by COMcheck-Web Software

THROUGHOUT CONSTRUCTION KEEP THE PROJECT SITE CLEAN AND NEAT. DO NOT ALLOW HAZARDOUS, DANGEROUS, OR UNSANITARY CONDITIONS OR PUBLIC NUISANCES TO DEVELOP OR PERSIST ON THE SITE.

APPROVAL OF WORK: PRESENCE OF THE OWNER ON THE JOB DOES NOT IMPLY APPROVAL OR ACCEPTANCE O THE WORK. CALL SPECIFIC ITEMS TO ARCHITECT'S ATTENTION IF APPROVAL OF THOSE ITEMS IS REQUESTED.

WARRANTEES: MANUFACTURERS STANDARD WARRANTEES SHALL APPLY TO ALL PRODUCTS INSTALLED. WHERE REQUIRED CONTRACTOR SHALL VERIFY THAT ALL PRODUCTS ARE INSTALLED IN A MANNER THAT COMPLIES WITH THE CONDITIONS OF THE MANUFACTURER'S WARRANTEE AND COMPLIES WITH

AT COMPLETION OF THE PROJECT AND PRIOR TO FINAL ACCEPTANCE PROVIDE A COMPLETE SET MANUFACTURER'S STANDARD WARRANTEES AND OPERATION AND MAINTENANCE INSTRUCTIONS. DEMONSTRATE TO THE OWNER PROCEDURES AND MAINTENANCE OF ALL EQUIPMENT.

101 St Helens Street

5033863050

St Helens, Oregon 97051

alpetersen@akaandesign.com

MISCELLANEOUS NOTES & SPECIFICATIONS

WOOD FRAMING:

FOR ADDITIONAL INFORMATION SEE STRUCTURAL DRAWINGS AND SPECIFICATIONS.

ALL WOOD IN PERMANENT CONTACT WITH CONCRETE SHALL BE PRESSURE TREATED PER NDS SPECIFICATIONS AND IN ACCORDANCE WITH ALL LOCAL CODES AND REGULATIONS.

ALL INTERIOR WOOD FRAMING SHALL BE KILN DRY LUMBER DOUGLAS FIR #2 OR BETTER UNLESS NOTED OTHERWISE.

ALL BEAMS SHALL HAVE A MINIMUM BEARING WIDTH OF 3"

ALL FLOOR BEAMS SHALL HAVE TRIPPLE STUDS UNDERNEATH BEARING POINT WITH POSITIVE CONNECTION.

FLOOR SYSTEM: ALL FLOORS SHALL BE COVERED WITH 23/32" MIN. APA RATED T&G PANELS OR TO MATCH EXISTING FLOOR SHEATHING, GLUED AND ATTACHED WITH 10d NAILS. NAILS SPACED AT 6" O.C. MIN. AT PANEL EDGES AND 12" O.C. ELSEWHERE.

PARTICLE BOARD UNDERLAYMENT: ANSI A208.1, GRADE M-2, EXTERIOR GLUE COMPLYING WITH GRADE PBU.

SPRAY FOAM INSULATION:

- 1. SPRAY POLYURETHANE FOAM: TWO- COMPONENT SPRAY POLYURETHANE
- CELLULAR PLASTIC FOAM, MEETING THE FOLLOWING PHYSICAL PROPERTIES: CORE DENSITY (ASTM D1622): MINIMUM 2PCF
- R-VALUE, MEASURED AT 75F MEAN TEMP: MINIMUM R6.0/INCH.

THERMAL RESISTANCE (ASTM C518): 140DEGREEF/90DAY AGED

- FLAME SPREAD (ASTM E84, CLASS A): 25 OR LESS. • SMOKE DEVELOPED (ASTM E84, CLASS A): 450 OR LESS.
- COMPRESSIVE STRENGTH MINIMUM: 20 PSI. CLOSED CELL CONTENT (ASTM D2856): MINIMUM 95 PERCENT.
- WATER ABSORPTION BY VOLUME MAXIMUM. (ASTM D2842): 2.5
- WATER VAPOR PERMEABILITY MAXIMUM. (ASTM E96): 2.5 PERM-INCHES
- 2. ACCEPTABLE PRODUCTS "STYROFOAM" SPRAY POLYURETHANE FOAM INSULATION (MX SERIES) OR APPROVED EQUAL.
- 3. PREPARATION: FOLLOW MANUFACTURER'S RECOMMENDATIONS FOR SURFACES CONDITIONS AND PREPARATION. OILY STEEL SURFACE LIKE Z-BAR, ROOF DECK, CURTAIN WALL PAN, ALUMINUM TUBE OR PVC PIPES CLEANING, ETCHING OR A PRIMER MAY BE NEEDED BEFORE SPRAYING POLYURETHANE FOAM.
- 4. MASK AND COVER ADJACENT AREAS TO PROTECT FROM OVERSPRAY. APPLY ANY REQUIRED PRIMERS FOR SPECIAL CONDITIONS AS RECOMMENDED BY MANUFACTURER. CLEAN AREA OF WORK PRIOR TO APPLICATION OF SPRAYED INSULATION. POST ALL REQUIRED WARNING
- . VERIFY EXISTING CONDITIONS ARE READY TO RECEIVE WORK ENSURE SURFACES ARE FREE OF FROST, OIL, GREASE, OXIDATION, DIRT, LOOSE PAINT, LOOSE SCALE, OR OTHER DELETERIOUS MATERIAL THAT WOULD IMPAIR BOND. ENSURE THAT ITEMS REQUIRED TO PENETRATE SPRAYED INSULATION ARE INSTALLED PRIOR TO INSTALLATION OF SPRAYED INSULATION.
- INSTALL FOAM PER MANUFACTURER'S SPECIFICATIONS WITH EQUIPMENT APPROVED BY THE FOAM MANUFACTURER FOR TYPE OF APPLICATION.
- 7. IMMEDIATELY CLEAN ANY OVER-SPRAY PER MANUFACTURE'S INSTRUCTIONS WITHOUT CAUSING DAMAGE.

POWER DOOR OPERATORS:

- 1. BASIS OF DESIGN PRODUCT: POWER DOOR OPERATORS FOR EXTERIOR SWINGING DOOR(S) - NORTON / ASSA-ABLOY 6300 SERIES LOW ENERGY
- 2. DOOR OPERATOR SHALL SIMULATE CONVENTIONAL DOOR CLOSER OPENING AND CLOSING FORCES UNLESS THE POWER OPERATOR MOTOR IS
- 3. OPERATOR SHALL HAVE SELECTABLE POWER CLOSE TO PROVIDE ADDITIONAL CLOSING FORCE TO OVERCOME CONDITIONS THAT MAY PREVENT DOOR FROM LATCHING.
- 4. THE UNIT SHALL BE ADJUSTABLE TO PROVIDE COMPLIANCE WITH THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT (ADA). UNIT SHALL BE CERTIFIED BY BHMA TO MEET A156.19 REQUIREMENTS. UNIT SHALL BE U.L. LISTED FOR AUTOMATIC CLOSING DOOR AND MEET UL325/991, UL10C STANDARDS.
- 5. UNIT SHALL HAVE A THREE-POSITION SELECTOR MODE SWITCH THAT WILL PERMIT THE UNIT TO BE SWITCHED "ON" TO MONITOR FOR FUNCTION INPUTS, SWITCH TO "H/O" FOR INFINITE HOLD OPEN FUNCTION OR SWITCHED "OFF" WHICH WILL DISABLE FUNCTION INPUTS ALLOWING UNIT TO BE USED AS A MANUAL DOOR CLOSER.
- 6. DOOR OPERATOR OPENING FORCE AND SPEED SHALL BE ADJUSTABLE TO ENSURE ADEQUATE OPENING CONTROL PER ACCESSIBILITY CODES. DOOR OPERATOR SHALL HAVE AN ADJUSTABLE TO CUSHION THE DOOR SPEED IF OPENED VIOLENTLY.
- 7. DOOR CLOSING FORCE SHALL BE ADJUSTABLE TO ENSURE ADEQUATE CLOSING CONTROL. DOOR CLOSING SPEED SHALL BE CONTROLLED BY INDEPENDENTLY FOR THE SWEEP AND LATCH RANGE OF THE CLOSING
- 8. DOOR OPERATOR SHALL BE SELECTIVELY ACTIVATED BY EXTERNAL INITIATING DEVICE, I.E. WALL SWITCH, ETC.
- 9. UNIT SHALL INCLUDE FEATURE TO AUTOMATICALLY RECOGNIZE ABLED BODY TRAFFIC AND IMMEDIATELY TRIGGER DOOR TO CLOSE AFTER SENSING NO FORCES ON DOOR.
- 10. UNIT SHALL HAVE DELAY SWITCHES FOR MOTOR ACTIVATION, ELECTRIC LOCK INTERFACING, AND HOLD OPEN TIME. UNITS SHALL INTERFACE WITH LATCH ASSIST EXIT DEVICES OR SIMILAR PRODUCTS AND HAVE 24VDC @ 1.3A MAXIMUM (LESS ACCESSORIES) OUTPUT FOR CONNECTION OF ELECTRIC STRIKE, LOCK, RADIO FREQUENCY RECEIVER, ETC.
- 11. UNITS SHALL BE CAPABLE OF VESTIBULE SEQUENCING INPUT FOR OPERATION OF TWO OR MORE UNITS. UNIT SHALL BE CAPABLE OF SMOKE VENTILATION INPUTS TO POWER OPEN DOORS WHEN ACTIVATED BY FIRE OR SMOKE ALARM. UNIT SHALL BE ETL TESTED TO UL STANDARDS FOR AUTOMATIC CLOSING DOOR.

12. FOR POWER OPERATOR FUNCTION: WHEN ACTIVATED, THE UNIT SHALL POWER OPEN THE DOOR AT BOTH A SPEED AND FORCE THAT ARE ADJUSTABLE TO ACCESSIBILITY CODES. THE DOOR SHALL BE POWERED FROM A DOOR CLOSED POSITION TO A FULL DOOR OPEN POSITION AND REMAIN IN MOMENTARY HOLD OPEN FOR 5 SECONDS MINIMUM AND ADJUSTABLE 0 TO 30 SECONDS IN 1 SECOND INCREMENTS. UNIT SHALL POWER OPEN DOOR TO FULL OPEN POSITION UP TO110°. UNIT SHALL BE CAPABLE OF OPENING DOOR MANUALLY FROM 110° - 180°. ONCE UNIT REACHES FULL HOLD OPEN POSITION, IF REINITIATED, UNIT'S MOMENTARY HOLD OPEN TIME SHALL RESTART FROM THE MAXIMUM SET TIME. IF UNIT IS INITIATED DURING THE CLOSING CYCLE, UNIT SHALL REVERT TO OPENING CYCLE BEGINNING AT THAT DOOR POSITION. UNIT SHALL HAVE A TOGGLED HOLD OPEN INPUT THAT UPON FIRST INITIATION

WILL POWER DOOR TO A MAINTAINED HOLD OPEN POSITION; A SECOND

13. UNIT SHALL HAVE OBSTRUCTION DETECTION ON CLOSING, WHICH WILL REVERSE THE CLOSING DOOR TO THE FULL OPEN POSITION THEN RE-ATTEMPT TO CLOSE DOOR AFTER MOMENTARY HOLD OPEN TIME HAS ELAPSED. OBSTRUCTION DETECTION ON OPENING SHALL SHUT MOTOR OFF, ALLOWING DOOR TO CLOSE UNDER SPRING FORCE. THESE OBSTRUCTION DETECTION FEATURES SHALL BE INTEGRAL TO UNIT. DURING CLOSING CYCLE, THE UNIT SHALL CLOSE DOOR UNDER FULL SPRING POWER NOT TO EXCEED A CLOSING FORCE OF 15 LBF.

INITIATION WILL ALLOW DOOR TO CLOSE.

VIDEO SURVEILLANCE SYSTEM:

PROVIDE AND INSTALL VIDEO SURVEILLANCE SYSTEM AS DESCRIBED BELOW. PROVIDE CABLING AS DESCRIBED IN PROJECT MANUAL AND PER THE BELOW.

WHERE THERE ARE EXISTING CABLE RUNS TO EXISTING CAMERAS, AND EXISTING CABLES ARE CAPABLE TO PROVIDE P.O.E. (POWER OVER ETHERNET)

SERVICE TO NEW CAMERAS EXISTING CABLES MAY BE UTILIZED.

FOR NEW CABLE RUNS PROVIDE P.O.E. CAT6 OR CAT6E CABLES TO EACH CAMERA LOCATION IN LENGTHS OF LESS THAN 300'.

CABLES CAN BE ROUTED TO EITHER EAST SIDE DISTRIBUTION RACK OR WEST SIDE PRIMARY SERVER RACK.

SUBMITTALS: PROVIDE MANUFACTURE'S DATA FOR ALL SYSTEM HARDWARE, CABLING, CABLE ATTACHMENTS, AND MOUNTING HARDWARE.

VERIFY ALL MOUNTING LOCATIONS, MOUNTING HEIGHTS, CAMERA AIMING, AND AND ANY EXPOSED WIRES WITH ARCHITECT AND OWNER PRIOR TO RUNNING CABLES AND INSTALLING HARDWARE.

IN SHOP (HIGH BAY) INSTALL ALL CABLING IN CONDUIT UNLESS PRIOR APPROVAL IS OBTAINED FOR EXPOSED WIRE MOUNTING.

PROVIDE THE FOLLOWING HARDWARE:

OUTDOOR CAMERAS: UNIFI G4 PRO SHOP CAMERAS (HIGH BAY): INIFI G3 PRO INTERIOR CAMERAS G3 FLEX FOR CEILING OR WALL MOUNT RECORDING DEVICE: CLOUD KEY GEN2 PLUS W/ MIN 4TB HARD DRIVE ACCESSORY: CLOUD KEY G2 RACK MOUNT ACCESSORY

OWNERS I.T. SUPPORT PERSONNEL WILL CONFIGURE SYSTEM AFTER SYSTEM IS INSTALLED.

FIRE PROTECTION SYSTEM:

- 1. FOR ADDITIONAL SPECIFICATIONS SEE PROJECT MANUAL.
 - 2. QUALITY ASSURANCE: DESIGN AND INSTALLATION SHALL CONFORM TO LOCAL BUILDING CODES AND NFPA-13.
 - SUBMITTALS: FIRE SPRINKLER INSTALLER SHALL BE RESPONSIBLE FOR SUPPLYING DESIGN AND DOCUMENTATION OF FIRE PROTECTION SYSTEM ALTERATIONS FOR ARCHITECT AND PLAN REVIEW.
 - 4. REGULATORY REQUIREMENTS: PRODUCT DATA, AND SHOP DRAWINGS SHALL BEAR A STAMP OF THE APPROVAL OF THE AUTHORITIES HAVING JURISDICTION INCLUDING BUT NOT LIMITED TO THE LOCAL BUILDING DEPARTMENT AND LOCAL FIRE MARSHAL.
 - 5. THE FIRE SPRINKLER CONTRACTOR SHALL BE RESPONSIBLE FOR THE DESIGN/INSTALLATION DRAWINGS. THE DESIGN SHALL COMPLY WITH NFPA-13, LATEST ADOPTED EDITION, AS WELL AS STATE AND LOCAL CODES THAT ARE APPLICABLE.
- 6. CONTRACTOR SHALL OBTAIN STATIC AND RESIDUAL WATER PRESSURE AND FLOW DATA PRIOR TO SYSTEM DESIGN AND SHALL SUBMIT RECENT FLOW TEST DATA WITH DRAWINGS AND CALCULATIONS.
- 7. ALL DRAWINGS AND CALCULATIONS SHALL BE SIGNED AND SEALED BY THE FIRE SPRINKLER CONTRACTOR'S REGISTERED FIRE SPRINKLER DESIGNER/ENGINEER.
- 8. SPRINKLER SYSTEM INSTALLATION CONTRACTOR SHALL SUBMIT SHOP DRAWINGS TO PLANS REVIEW OFFICE FOR REVIEW, VERIFICATION, AND PERMANENT RECORD PRIOR TO INSTALLATION.
- 9. INSTALLATION CONTRACTOR SHALL PERFORM ALL REQUIRED PRESSURE AND ACCEPTANCE TESTING. MATERIAL AND TEST CERTIFICATE(S) SHALL BE SUBMITTED TO THE AUTHORITIES HAVING JURISDICTION PRIOR TO ASKING FOR APPROVAL OF THE INSTALLATION. COPIES SHALL BE SUBMITTED TO OWNER AND ARCHITECT.
- 10. COORDINATE INSTALLATION OF SPRINKLERS AND PIPING SYSTEMS TO AVOID FREEZING CONDITIONS. NOTIFY ARCHITECT OF AREAS FOR WHERE SYSTEM MAY BE EXPOSED TO FREEZING. INSTALL DRY SPRINKLERS IN ROOMS THAT MAY BE UNCONDITIONED OR EXPOSED TO FREEZING CONDITIONS. PROVIDE AUXILIARY DRAINS WHERE REQUIRED.
- 11. INSTALLATION CONTRACTOR SHALL INSPECT SITE AND CHECK ALL EXISTING CONDITIONS PRIOR TO BIDDING AND COORDINATE FIRE SPRINKLER INSTALLATION WITH EXISTING CONDITIONS. CONTRACTOR SHALL NOTIFY OWNER AND ARCHITECT OF ANY CONDITIONS THAT MAY CONFLICT WITH FIRE SPRINKLER INSTALLATION.
- 12. ARCHITECTURAL DRAWINGS ARE SCHEMATIC IN NATURE, INTENDED TO CONVEY THE SCOPE OF WORK AND GENERAL ARRANGEMENT OF THE SYSTEM. SPRINKLER SYSTEMS CONTRACTOR SHALL COORDINATE SPRINKLER SYSTEM ARRANGEMENT WITH ARCHITECTURAL STRUCTURAL, MECHANICAL AND ELECTRICAL COMPONENTS. SPRINKLER PIPING SHALL NOT BE INSTALLED BELOW MECHANICAL EQUIPMENT OR WITHIN CLEARANCE SPACES FOR MECHANICAL EQUIPMENT. INSTALLATION CONTRACTOR SHALL BE RESPONSIBLE FOR ANY MODIFICATIONS TO THE SYSTEM TO AVOID CONFLICTS.
- 13. SUBMITTALS: PROVIDE DETAILED PIPE LAYOUT, HANGER AND SUPPORTS, COMPONENTS AND ACCESSORIES. SUBMIT SHOP DRAWINGS, PRODUCT DATA TO AUTHORITY HAVING JURISDICTION AND FIRE MARSHAL FOR APPROVAL PRIOR TO SUBMISSION TO ARCHITECT.
- 14. PRODUCTS: ALL PRODUCTS AND SYSTEM COMPONENTS AND METHODS OF HANGING PIPE, HEADERS, BRANCHES, AND BRACING SHALL BE APPROVED AND IN CONFORMANCE WITH NFPA-13. FOR PRODUCTS NOT LISTED IN NFPA-13 CONTRACTOR SHALL SUBMIT WHITE PAPERS OR OTHER APPROVAL DOCUMENTS FROM UNDERWRITERS LABORATORIES AND BEAR THE UL MARK.
- 15. MATERIAL SUBMITTALS SHALL BE SUBMITTED TO ARCHITECT FOR APPROVAL PRIOR TO ANY INSTALLATION.



PROJECT TEAM:

CIVIL ENGINEER AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way

Scappoose, Oregon 97056 503-983-0573 \Box

 $\leq \infty$

NUFACTUF CENTER R

SCALE: AS NOTED DRAWN BY: CHECKED BY: CAD FILE: 208A_A10 DATE: 03/26/2020

REVISIONS DESCRIPTION DATE

CONTENTS:

NAILING SCHEDULE

SHEET NO:

Energy Code: 2014 Oregon Energy Efficiency Specialty Code Project Title: OMIC R&D Retrofit Project Type: Alteration Envelope Compliance Method: Prescriptive Construction Site: Designer/Contractor: Owner/Agent: 33701 Charles T Parker Way Oregon Manufacturing & Innovation AKAAN Architecture + Design LLC

33701 Charles T Parker Way

Scappoose, Oregon 97056

Center R&D

503-543-3306 Building Location (for weather data): Scappoose, Oregon Climate Zone: Pct. Window and Glass Door Area Replaced: 20% Building Use: Area Type

Section 1: Project Information

Scappoose, Oregon 97051

Section 2: Envelope Assemblies and Requirements Checklist

1-High Bay / Machine Floor (Manufacturing Facility/Data Center): 27000

nvelope PASSES						
Envelope Assemblies:						
	R-V	alue	Prope	osed	Max. Al	lowed
Post-Alteration Assembly	Cavity	Cont.	U-Factor	SHGC	U-Factor	SHGC
Roof: Metal Building, Screw Down, [Bldg. Use 1 - High Bay / Machine Floor]	28.0	11.4	0.048		0.055	-
Ext. Wall: Metal Building Wall, [Bldg. Use 1 - High Bay / Machine Floor]	21.0	13.0	0.035		0.069	-
Door: Insulated Metal, Non-Swinging, [Bldg. Use 1 - High Bay / Machine Floor]			0.380		0.500	_
Window: Metal Frame, Clear, [Bldg. Use 1 - High Bay / Machine Floor], Exemption: Less than 25% fenestration area alteration.						
Window: Metal Frame, Clear, [Bidg. Use 1 - High Bay / Machine						_

Floor Area

Floor], Exemption: Less than 25% fenestration area alteration. (a) Fenestration product performance must be certified in accordance with NFRC and requires supporting documentation

In the following requirements, blank checkboxes identify requirements that the applicant has not acknowledged as being met. Checkmarks identify requirements that the applicant acknowledges are met or excepted from compliance. 'Plans reference page/section' identifies where in

the plans/specs the requirement can be verified as being satisfied.

Fenestration Product Rating: 1. U-factors of fenestration products (windows, doors and skylights) are determined in accordance with NFRC 100 by an accredited, independent laboratory, and labeled and certified by the manufacturer or are determined using the commercial size category values listed in Chapter 15 of the 2009 ASHRAE Handbook of Fundamentals, Table No.4 and shall include the effects of the window frame. The temporary label afixed to the fenestration products must not be removed prior to inspection.

2. Solar heat gain coefficient (SHGC) of glazed fenestration products (windows, glazed doors and skylights) shall be determined in

Plans reference page/section: Project Manual - Division 08-45-23 & 08-51-13

overall values must consider type of frame material and operator for the SHGC at normal incidence. Plans reference page/section: Project Manual - Division 08-45-23 & 08-51-13

Air Leakage, Insulation, and Component Certification:

Project Title: OMIC R&D Retroff Report date: 02/03/20 Data filename:

accordance with NFRC 200 by an accredited, independent laboratory, and labeled and certified by the manufacturer or be determined using the Solar Heat Gain Coefficients (SHGC) in Chapter 15 of the 2009 ASHRAE Handbook of Fundamentals, Table No.10. The

3. Sealing of the building envelope. Openings and penetrations in the building envelope are sealed with caulking materials or closed with gasketing systems compatible with the construction materials and location. Joints and seams are sealed in the same manner or taped or covered with a moisture vapor-permeable wrapping material. Sealing materials spanning joints between construction materials allow for expansion and contraction of the construction materials.

entrance doors and revolving doors are tested for air leakage in accordance with ASTM E 283. For curtain walls and storefront glazing, the maximum air leakage rate is 0.3 cubic foot per minute per square foot of fenestration area. For commercial glazed swinging entrance doors and revolving doors, the maximum air leakage rate is 1.00 cfm/ft2 of door area.

nches or greater in width. Alternately, the insulation installers have provided a signed, dated and posted certification listing the type, manufacturer and R-value of insulation installed. Refer to code section for blown or sprayed insulation installation/settling depths and

✓ 7. Insulation mark installation. Insulating materials are installed such that the manufacturer's R-value mark is readily observable upon

9. Installation. All material, systems and equipment are installed in accordance with the manufacturer's installation instructions and the 10.Outdoor air intakes and exhaust openings. Stair and elevator shaft vents and other outdoor air intakes and exhaust openings integral

are parked in the doorway.

Plans reference page/section: ___ 🏏 11.Loading dock weatherseals. Cargo doors and loading dock doors are equipped with weather seals to restrict infiltration when vehicles

sealed with a gasket or caulk between the housing and interior wall or ceiling covering. Requirement is not applicable

rigid insulation must be installed between the metal wall panel and steel framing, or on the interior of the steel framing. See Table

Plans reference page/section: Existing 🛩 14.Vestibules. Doors that separate conditioned space from the exterior are protected with an enclosed vestibule, with all doors of the vestibule equipped with self-closing devices. Vestibules are designed so interior and exterior doors to not operate simultaneously.

✓ 15. Other components have supporting documentation for proposed U-Factors. Requirement is not applicable

Plans reference page/section: Project Manual - Division 08-45-23 & 08-51-13

4. Window and door assemblies. The air leakage of window and sliding or swinging door assemblies that are part of the building envelope are determined in accordance with AAMA/WDMA/CSA 101/I.S.2/A440, or NFRC 400 by an accredited, independent laboratory, and

Plans reference page/section: Project Manual - Division 08-45-23 & 08-51-13 5. Curtain wall, storefront glazing and commercial entrance doors. Curtain wall, storefront glazing and commercial-glazed swinging

Plans reference page/section: Project Manual - Division 08-45-23 & 08-51-13

🥒 6. Building thermal envelope insulation. An R-value identification mark is applied (by manufacturer) to each piece of insulation 12

🇸 8. Insulation product rating. The thermal resistance (R-value) of insulation has been determined in accordance with the U.S. FTC R-value

to the building envelope shall be equipped with not less than a Class I motorized, leakage-rated damper with a maximum leakage rate of 4 cfm per square foot at 1.0 inch water gauge when tested in accordance with AMCA 500D. Stair and shaft vent dampers shall be capable of being automatically closed during normal building operation and interlocked to open as required by fire and smoke detection

Requirement is not applicable

Plans reference page/section: Project Manual - Division 08-36-13 🛩 12.Recessed lighting. Recessed luminaires installed in the building thermal envelope are sealed to limit air leakage between conditioned and unconditioned spaces. All recessed luminaires are IC-rated and labeled as meeting ASTM E 283. All recessed luminaires are

Plans reference page/section: _____ 🗸 13.Metal building wall insulation must include a fibergiass layer installed between the metal wall panels and the steel framing. Continuous

Requirement is not applicable.

Exception applies: Doors used primarily to facilitate vehicular movement or material handling and adjacent personnel doors. Plans reference page/section: _____

Plans reference page/section: .

Section 3: Compliance Statement

Project Title: OMIC R&D Retrofit

Data filename:

Compliance Statement: The proposed envelope alteration project represented in this document is consistent with the building plans, specifications and other calculations submitted with this permit application. The proposed envelope alteration project has been designed to meet the 2014 Oregon Energy Efficiency Specialty Code requirements in COMcheck-Web and to comply with the mandatory requirements in

Project Notes: Renovation of Existing Building

Report date: 02/03/20

FOR PERMIT

200A — STORAGE 87 SQ FT

1 OCC

==========

OFFICE 281 SQ FT OFFICE 3 OCCUPANTS 1:100

AR/VR CLASSROOM 662 SQ FT B 33 OCCUPANTS 1:20

ELEVATOR

200 MEETING ROOM 1318 SQ FT

88 OCCUPANTS 1:15

> 201 OFFICE 254 SQ FT

B 3 OCCUPANTS 1:100

202 OFFICE 254 SQ FT B 3 OCCUPANTS 1:100

203 OFFICE 254 SQ FT B 3 OCCUPANTS 1:100

204 OFFICE 268 SQ FT

3 OCCUPANTS 1:100

UPPER FLOOR EAST 1/8" = 1'-0"

UPPER FLOOR ADMINISTRATIVE OFFICE AREA: 4,186 SQ. FT. OCCUPANT LOAD 137

OFFICE 268 SQ FT OCC TYPE - B OCC LOAD 3 1:100 BREAK RM
303 SQ FT|
0CC TYPE - B
0CC LOAD 2Q
1:15 OFFICE
254 SQ FT
OCC TYPE - B
OCC LOAD 3
1:100 WOMEN'S RESTROOM 108 EXIT PATH MEN'S RESTROOM 162 SQ FT OFFICE
254 SQ FT
OCC TYPE - B
OCC LOAD 3
1:100 112 OFFICE 200 SQ FT OCC - B OFFICE
254 SQ FT
OCC TYPE - B
OCC LOAD 3
1:100 OFFICE
254 SQ FT
OCC TYPE - B
OCC LOAD 3
1:100 116 HALL FIRE DEPARTMENT CONTROL PANEL

SCOPE OF WORK:
RENOVATION OF EXISTING OFFICE AREA TO INSTALL AN ELEVATOR FOR ADA ACCESS TO UPPER LEVEL OFFICE AREA AND INSTALL AN EGRESS STAIR FROM THE UPPER LEVEL MEETING ROOM WHICH EXCEEDS AN OCCUPANT LOAD OF 49 OCCUPANTS.

THE EXISTING BUILDING IS FULLY SPRINKLERED PER NFPA-13, AND HAS A FIRE ALARM SYSTEM.

LEGEND

© DIRECTIONAL EGRESS SIGN

© EXIT SIGN

© EMERGENCY LIGHTING

OF OCCUPANTS
& DIRECTION OF
TRAVEL

NUMBER OF EXITS REQUIRED IN EACH ROOM OR AREA:

-PER OSSC TABLE 1015.1: A-2 & B OCCUPANCY ROOMS WITH OCCUPANT LOAD
OF 49 OR LESS REQUIRE ONE EXIT. S-1 OCCUPANCY ROOMS WITH OCCUPANT
LOAD OF 29 OR LESS REQUIRE ONE EXIT.

NUMBER OF EXITS PROVIDED IN EACH ROOM OR AREA:

-ONE EXIT IS PROVIDED FROM EACH ROOM WITHIN THE BUILDING.

-TWO EXITS PROVIDED TO EXTERIOR FROM ADMINISTRATIVE OFFICE SUITE.

-TWO EXITS PROVIDED FROM UPPER LEVEL MEETING ROOM

MAX EXIT PATH IN EACH ROOM OR AREA:
-LONGEST EXIT PATH FROM ANY SPACE IS 20'-0" TO EXIT ACCESS.

EST EXIT PATH ON EACH FLOOR:

- LONGEST EXIT PATH FROM FURTHEST MAIN FLOOR OFFICE/STORAGE ROOM IS 95' TO THE EXTERIOR, MAX ALLOWED PER 1017.2 IS 350'.

-LONGEST EXIT PATH FROM FURTHEST UPPER FLOOR OFFICE/STORAGE ROOM IS 163', MAX ALLOWED PER 1017.2 IS 250'.

- LONGEST COMMON PATH OF TRAVEL FROM FURTHEST UPPER FLOOR OFFICE/STORAGE ROOM IS 88', MAX ALLOWED PER 1006.2.1 IS 100'.

COMPONENT WIDTHS:

STAIRS: 0.3" PER OCCUPANT = 32" REQUIRED,
48" PROVIDED

48" PROVIDED

OTHER COMPONENTS: 0.2" PER OCCUPANT= 16" MIN REQD,
36" PROVIDED

MEANS OF EGRESS			
# OF EXIITS			
GROUND FLOOR	2 MIN	2 PROVIDED	1015
UPPER FLOOR	2 MIN	2 PROVIDED	
EXIT ACCESS STAIRWAYS	ALLOWED	PROVIDED	1019.3.1
DEAD END CORRIDORS	50' MAX	41'	1020.4 EXCEPTION 2
EGRESS CORRIDOR WIDTH	44 MIN		1009
OTHER COMPONENTS WIDTH	36 MIN		ADA
FIRE PROTECTION SYSTEMS			
	REQUIRED	PROPOSED	
AUTOMATIC SPRINKLERS	REQUIRED	EXISTING	903
ALT. EXTINGUISHING SYS.	NOT REQUIRED	NA	904
STANDPIPE SYS.	NOT REQUIRED	NA	905
FIRE ALARM & DETECTION	NOT REQUIRED	EXISTING	907.2.4
EMERGENCY ALARMS	NOT REQUIRED	NA	908

LOWER FLOOR ADMINISTRATIVE OFFICE AREA: 4,570 SQ. FT. OCCUPANT LOAD 46

COMBINED FLOORS BUSINESS OFFICE SUITE - TOTAL OCCUPANT LOAD 183

architecture + design IIc

WILLIAM ALLAN
PETERSEN
ST. HELENS, OREGON
OF OREGON

101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3

PROJECT TEAM:

CIVIL ENGINEER:
AKS ENGINEERING & FORESTRY
12965 SW Herman Road, Suite 100
Tualatin, OR 97062
P: 503.563.6151
F: 503.563.6152

STRUCTURAL ENGINEER:
PETERSON STRUCTURAL ENGINEERS
9400 SW Barnes Road, Suite 100
Portland, OR 97225
P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER:
OMIC R&D / OREGON TECH.
Procurement and Contract Services
27500 SW Parkway Avenue
Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way Scappoose, Oregon 97056 503-983-0573

> OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE: AS NOTED
DRAWN BY: AP
CHECKED BY: AP
CAD FILE: 1404_FLS-1.dwg
DATE: APRIL 15,2020

REVISIONS

A DATE DESCRIPTION

CONTENTS:

FIRE / LIFE SAFETY PLAN (east offices)

SHEET NO:

FLS-1

WILLIAM ALLAN
PETERSEN

OF OREGON

OF OREGON

01 ST HELENS ST T HELENS, OR 97051 : 503 366 3050 F: 503 3

PROJECT TEAM:

CIVIL ENGINEER:
AKS ENGINEERING & FORESTRY
12965 SW Herman Road, Suite 100
Tualatin, OR 97062
P: 503.563.6151
F: 503.563.6152

STRUCTURAL ENGINEER:
PETERSON STRUCTURAL ENGINEERS
9400 SW Barnes Road, Suite 100
Portland, OR 97225
P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER:
OMIC R&D / OREGON TECH.
Procurement and Contract Services
27500 SW Parkway Avenue
Wilsonville, OR 97070

OWNER'S REPRESENTATIVE:
CRAIG CAMPBELL, Executive Director
OMIC R&D
33701 Charles T. Parker Way
Scappoose, Oregon 97056
503-983-0573

OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE: AS NOTED
DRAWN BY: AP
CHECKED BY: KP
CAD FILE: 1404-SITEPLAN-3A.DWG
DATE: 03/08/2020

REVISIONS

DATE DESCRIPTION


1 04/08/2020 PARKING RECONFIG

CONTENTS:

SITE PLAN

SHEET NO:

SP1.1



101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3

WILLIAM ALLAN PETERSEN ST. HELENS, OREGON

PROJECT TEAM:

CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way Scappoose, Oregon 97056

503-983-0573

AS NOTED SCALE: DRAWN BY: CHECKED BY: CAD FILE: 1404-SP12.DWG DATE:


REVISIONS DATE DESCRIPTION

CONTENTS:

SITE DETAILS

SHEET NO:

SP1.2



101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3 WILLIAM ALLAN PETERSEN ST. HELENS, OREGON PROJECT TEAM: CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152 STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635 MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030 OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070 OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D

OREGON MANUFACTURING INNOVATION CENTER R & D

33701 Charles T. Parker Way

Scappoose, Oregon 97056

503-983-0573

SCALE: AS NOTED
DRAWN BY: AP
CHECKED BY: KP
CAD FILE: 1404-FLOOR-1.DWG
DATE: JAN. 28, 2020

REVISIONS

___ DATE DESCRIPTION


CONTENTS:


FIRST FLOOR DEMOLITION PLAN

SHEET NO:

A0.1

ELEVATIONS





SCALE: DRAWN BY: CHECKED BY: CAD FILE: DATE:

1404-FLOOR-2.DWG JAN. 28, 2020 REVISIONS ______ DATE DESCRIPTION

AS NOTED

CONTENTS:

SECOND FLOOR DEMOLITION PLAN

SHEET NO:

A0.2

RENOVATION NOTES:

- 1. SALVAGED WOOD BASE FROM HALLS TO BE USED TO REPAIR WOOD BASE IN ROOMS AS REQUIRED, NEW WALL BASE THROUGHOUT ALL HALLWAYS AND WEST WING SECOND FLOOR HALL AND ADA LIFT
- WITH TRIM SHOWN ON DRAWING 13/A4.4, PAINT.
- A RENOVATION KEYNOTES:
- A. INSTALL NEW OVERHEAD DOOR & AUTOMATIC
- B. INFILL WALL W/ STEEL STUDS & EXTERIOR PHENOLIC PANELS BELOW W/ WITH KALWALL TRANSLUCENT WALL SYSTEM ABOVE
- C. INFILL WALL W/ STEEL STUD WALL & EXTERIOR SHEETMETAL SIDING
- D. INFILL WALL W/ STEEL STUDS & EXTERIOR SHEETMETAL PANELS BELOW W/ WITH ALUMINUM WINDOWS ABOVE
- E. NEW METAL TRIM AT HIGH BAY MAN DOORS F. INSTALL NEW HOLLOW METAL FRAMES AND SOLID CORE WOOD INTERIOR DOORS WHERE INDICATED, SEE DOOR SCHEDULE
- G. NEW ELECTRICAL RACEWAY CABLE TRAYS & POSTS H. NEW WOOD FRAMED WALLS. I. NEW 2500# "HOLE-LESS" TWO-STOP ELEVATOR BASIS OF DESIGN OTIS — HYDROFIT
- J. NEW 90 DEGREE MID SIZED CHAIR LIFT WITH AUTOMATIC DOORS. K. ENTRY LOBBY, NEW CUSTOM RECEPTION DESK, NEW FLOOR FINISH COMMERCIAL LUXURY VINYL TILE, NEW CEILING FINISHES (METAL MESH, WOOD & STEEL PANELS), NEW LIGHTING - PENDANT
- AND RECESSED, FLAT SCREEN LED DISPLAYS. L. EXISTING FIRE SPRINKLER CONTROLS, MODIFY SYSTEM AS REQUIRED, SEE MECHANICAL DRAWINGS M. SLOPE FLOOR TO LEVEL OF LIFT (3"). N. INSTALL NEW STEEL HANDRAILS
- O. NEW MECHANICAL UNITS SEE MECHANICAL DWGS P. DUCT PENETRATIONS IN WALLS SEE MECHANICAL
- Q. NEW LVT FLOORING R. INFILL WALL MTL STUDS, SHEATH EXTERIOR TO
- MATCH EXISTING. S. ROOM 120-121 REPAIR WALLS, CEILING & FLOOR, T, DOOR 107 - INSTALL ELECTRONIC/MAGNETIC LOCK REMOVE KEYED LATCH.
- # DOOR SYMBOL SEE DOOR SCHEDULE
- X WINDOW SYMBOL SEE WINDOW TYPES
- SIGNAGE SYMBOL.

 D = DIRECTIONAL SIGN. SEE A4.2

 M = MESSAGE SIGNAGE

 R = ROOM SIGNAGE. SEE A4.2
- REVISION SYMBOL

2. WHERE LVT IS INSTALLED POUR SELF LEVELING COMPOUND AS REQD TO MATCH LEVEL OF EXISTING FLOOR TILE.

3. REMOVE EXISTING WOOD TRIM ON THE CORRIDOR SIDE OF ALL INTERIOR OFFICE WINDOWS, REPLACE

> WILLIAM ALLAN PETERSEN ST. HELENS, OREGON A

101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3

PROJECT TEAM:

CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director 33701 Charles T. Parker Way Scappoose, Oregon 97056 503-983-0573

OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE: DRAWN BY: CHECKED BY: CAD FILE: DATE:

1404-Floor1 APRIL 3, 2020

1/8" = 1'-0"

REVISIONS DATE DESCRIPTION 1 04/15/2020 PER BLDG OFFICIAL

CONTENTS:

FIRST FLOOR PLAN EAST

SHEET NO:

RENOVATION NOTES:

- COMPOUND AS REQD TO MATCH LEVEL OF EXISTING FLOOR TILE.
- SIDE OF ALL INTERIOR OFFICE WINDOWS, REPLACE WITH TRIM SHOWN ON DRAWING 13/A4.4, PAINT.

A RENOVATION KEYNOTES:

- A. INSTALL NEW OVERHEAD DOOR & AUTOMATIC OPERATOR
- B. INFILL WALL W/ STEEL STUDS & EXTERIOR PHENOLIC PANELS BELOW W/ WITH KALWALL TRANSLUCENT WALL SYSTEM ABOVE
- C. INFILL WALL W/ STEEL STUD WALL & EXTERIOR SHEETMETAL SIDING
- D. INFILL WALL W/ STEEL STUDS & EXTERIOR SHEETMETAL PANELS BELOW W/ WITH ALUMINUM WINDOWS ABOVE
- NEW METAL TRIM AT HIGH BAY MAN DOORS F. INSTALL NEW HOLLOW METAL FRAMES AND SOLID CORE WOOD INTERIOR DOORS WHERE INDICATED, SEE DOOR SCHEDULE
- G. NEW ELECTRICAL RACEWAY CABLE TRAYS & POSTS H. NEW WOOD FRAMED WALLS.
- I. NEW 2500# "HOLE-LESS" TWO-STOP ELEVATOR BASIS OF DESIGN OTIS - HYDROFIT
- J. NEW 90 DEGREE MID SIZED CHAIR LIFT WITH AUTOMATIC DOORS.
- K. ENTRY LOBBY, NEW CUSTOM RECEPTION DESK, NEW FLOOR FINISH COMMERCIAL LUXURY VINYL TILE, NEW CEILING FINISHES (METAL MESH, WOOD & STEEL PANELS), NEW LIGHTING - PENDANT AND RECESSED, FLAT SCREEN LED DISPLAYS.
- L. EXISTING FIRE SPRINKLER CONTROLS, MODIFY SYSTEM AS REQUIRED, SEE MECHANICAL DRAWINGS
- M. SLOPE FLOOR TO LEVEL OF LIFT (3"). N. INSTALL NEW STEEL HANDRAILS
- NEW MECHANICAL UNITS SEE MECHANICAL DWGS P. DUCT PENETRATIONS IN WALLS SEE MECHANICAL
- Q. NEW LVT FLOORING
- R. INFILL WALL W/ VINYL WINDOW TO MATCH EXISTING WITH FIBER CEMENT EXTERIOR WALL PANEL BELOW.


 S. ROOM 120–121 REPAIR WALLS, CEILING & FLOOR,
 EPOXY FLOOR TO MATCH HIGH-BAY
- # DOOR SYMBOL SEE DOOR SCHEDULE
- X WINDOW SYMBOL SEE WINDOW TYPES
- SIGNAGE SYMBOL.

 D = DIRECTIONAL SIGN. SEE A4.2

 M = MESSAGE SIGNAGE

 R = ROOM SIGNAGE. SEE A4.2

- 1. SALVAGED WOOD BASE FROM HALLS TO BE USED TO REPAIR WOOD BASE IN ROOMS AS REQUIRED, NEW WALL BASE THROUGHOUT ALL HALLWAYS AND WEST WING SECOND FLOOR HALL AND ADA LIFT
- 2. WHERE LVT IS INSTALLED POUR SELF LEVELING
- 3. REMOVE EXISTING WOOD TRIM ON THE CORRIDOR



101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3

PROJECT TEAM:

CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way Scappoose, Oregon 97056

OREGON MANUFACTURING INNOVATION CENTER R & D

503-983-0573


SCALE: 1/8" = 1'-0" DRAWN BY: CHECKED BY: CAD FILE: 1404-FLOOR-1.DWG

DATE: JAN. 28, 2020 REVISIONS ✓ DATE DESCRIPTION

CONTENTS:

FIRST FLOOR PLAN WEST

SHEET NO:



architecture + design IIc

101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3



PROJECT TEAM:

CIVIL ENGINEER:
AKS ENGINEERING & FORESTRY
12965 SW Herman Road, Suite 100
Tualatin, OR 97062
P: 503.563.6151
F: 503.563.6152

STRUCTURAL ENGINEER:
PETERSON STRUCTURAL ENGINEERS
9400 SW Barnes Road, Suite 100
Portland, OR 97225
P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER:
OMIC R&D / OREGON TECH.
Procurement and Contract Services
27500 SW Parkway Avenue
Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way Scappoose, Oregon 97056 503-983-0573

OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE: 1/8" = 1'-0"

DRAWN BY: AP

CHECKED BY: .

CAD FILE: 1404-FLOOR-2.DWG

DATE:

REVISIONS

A DATE DESCRIPTION

1 04/03/2020 PER BLDG OFF REV

CONTENTS:

SECOND FLOOR PLAN EAST

SHEET NO:

RENOVATION KEYNOTES:

A. INSTALL NEW HOLLOW METAL FRAMES AND SOLID CORE WOOD INTERIOR DOORS
B. NEW WOOD FRAMED WALLS.

C. NEW 2500# "HOLE-LESS" TWO-STOP ELEVATOR
D. NEW 90 DEGREE MID SIZED CHAIR LIFT WITH AUTOMATIC DOORS.

E. NEW RESTROOM F. NEW 5-TON OVERHEAD CRANE AND RUNWAY RAILS HUNG FROM EXISTING STEEL BRACKETS G. REPAIR FLOOR, NEW CARPET TILE H. NEW BEAMS IN ATTIC SPACE ABOVE CEILING
I. NEW FRAMING IN WALL FOR BEAM SUPPORT AS

J. REPLACE EXISTING COUNTERTOP & VANITIES W/ SOLID SURFACE WALL HUNG ADA ACCESSIBLE COUNTERTOPS AND UNDERMOUNT SINKS, REPAIR TILE & WALL FINISHES AS REQUIRED

K. 8" INSULATION INSTALLED BETWEEN EXISTING 8" ROOF GIRTS AND WALL GIRTS, WITH REINFORCED VAPOR BARRIER. L. COMMERCIAL LUXURY VINYL TILE

M. REPAIR CEILING N. REPAIR FLOOR WHERE FIXTURES REMOVED WITH TILE TO MATCH, REPAIR DRYWALL, PAINT

O. (NOT USED)
P. INSTALL CEILING MOUNTED EXIT LIGHT MATCHING EXISTING.

SIGNAGE SYMBOL.
D = DIRECTIONAL SIGN. SEE A4.2 M = MESSAGE SIGNAGE.R = ROOM SIGNAGE. SEE A4.2. SEE DOOR SCHED.

WILLIAM ALLAN PETERSEN ST. HELENS, OREGON OF OREGON

101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3

PROJECT TEAM:

CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way

Scappoose, Oregon 97056 503-983-0573 OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE: 1/8" = 1'-0" DRAWN BY: CHECKED BY: CAD FILE: 1404-FLOOR-2.DWG


DATE: JAN. 28, 2020 REVISIONS

△ DATE DESCRIPTION

CONTENTS:

SECOND FLOOR PLAN WEST

SHEET NO:



ATTIC FLOOR PLAN 1/8" = 1'-0"

WILLIAM ALLAN Y PETERSEN ST. HELENS, OREGON OF OREGON PROJECT TEAM: CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152 STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635 MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030 OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070 OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way Scappoose, Oregon 97056 503-983-0573

101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3

OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE: AS NOTED
DRAWN BY: AP
CHECKED BY: .
CAD FILE: 1404-FloorAttic.dwg
DATE: JAN. 28, 2020


REVISIONS


DATE DESCRIPTION


CONTENTS:

ATTIC FLOOR PLAN

SHEET NO:







architecture + design IIc

101 ST HELENS ST
ST HELENS, OR 97051
T: 503 366 3055



PROJECT TEAM:

CIVIL ENGINEER:
AKS ENGINEERING & FORESTRY
12965 SW Herman Road, Suite 100
Tualatin, OR 97062
P: 503.563.6151
F: 503.563.6152

STRUCTURAL ENGINEER:
PETERSON STRUCTURAL ENGINEERS
9400 SW Barnes Road, Suite 100
Portland, OR 97225
P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER:
OMIC R&D / OREGON TECH.
Procurement and Contract Services
27500 SW Parkway Avenue
Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way Scappoose, Oregon 97056 503-983-0573

> OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE:
DRAWN BY:
CHECKED BY:
CAD FILE:
DATE:

KP . 1404-A22.DWG JAN. 28, 2020

AS NOTED

REVISIONS


A DATE DESCRIPTION

CONTENTS:

BLDG ELEVATIONS ENTRIES

SHEET NO:

A2.2



101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3 ST. HELENS, OREGON PROJECT TEAM: CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152 STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635 MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way Scappoose, Oregon 97056 503-983-0573

OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE: AS NOTED DRAWN BY: CHECKED BY: CAD FILE: 1404-A22_A31.DWG


REVISIONS DATE DESCRIPTION 1 03/26/2020 FOR BLDG OFF REV

CONTENTS:


BUILDING SECTIONS

SHEET NO:

A3.1



101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3



PROJECT TEAM:

CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way Scappoose, Oregon 97056 503-983-0573

OREGON MANUFACTURING INNOVATION CENTER R & D

AS NOTED SCALE: DRAWN BY: CHECKED BY: CAD FILE: 1404-A32.DWG


DATE: JAN. 28, 2020 REVISIONS ∆ DATE DESCRIPTION

CONTENTS:

EXTERIOR DETAILS

SHEET NO:

A3.2



architecture + design IIc

101 ST HELENS ST
ST HELENS, OR 97051
T: 503 366 3055 F: 503 366 3055

WILLIAM ALLAN
PETERSEN
ST. HELENS, OREGON
OF OREGON

PROJECT TEAM:

CIVIL ENGINEER:
AKS ENGINEERING & FORESTRY
12965 SW Herman Road, Suite 100
Tualatin, OR 97062
P: 503.563.6151
F: 503.563.6152

STRUCTURAL ENGINEER:
PETERSON STRUCTURAL ENGINEERS
9400 SW Barnes Road, Suite 100
Portland, OR 97225
P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER:
OMIC R&D / OREGON TECH.
Procurement and Contract Services
27500 SW Parkway Avenue
Wilsonville, OR 97070

OWNER'S REPRESENTATIVE:
CRAIG CAMPBELL, Executive Director
OMIC R&D
33701 Charles T. Parker Way
Scappoose, Oregon 97056
503-983-0573

OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE: AS NOTED
DRAWN BY: KP
CHECKED BY: AP
CAD FILE: 1404-A33.DWG
DATE:

REVISIONS

DATE DESCRIPTION


1 03/26/2020 FOR BLDG OFF REV

CONTENTS:

EXTERIOR DETAILS

SHEET NO:

A3.3



EXG BLDG

101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3

WILLIAM ALLAN PETERSEN ST. HELENS, OREGON

PROJECT TEAM:

CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director 33701 Charles T. Parker Way

503-983-0573 \Box OREGON MANUFACTURININNOVATION CENTER R &


SCALE: AS NOTED DRAWN BY: CHECKED BY: CAD FILE: 1404-A41.DWG DATE:

REVISIONS DESCRIPTION DATE 1 03/26/2020 FOR BLDG OFF REV

CONTENTS:

ENLARGED PLANS, **SECTIONS & DETAILS**

SHEET NO:



SALVAGE WOOD BASE & TRIM FROM

chitecture + design IIc

101 ST HELENS ST
ST HELENS, OR 97051
T: 503 366 3050 F: 503 366 3055

WILLIAM ALLAN
PETERSEN

OF OREGON

OF OREGON

PROJECT TEAM:

CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER:
PETERSON STRUCTURAL ENGINEERS
9400 SW Barnes Road, Suite 100
Portland, OR 97225
P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER:
OMIC R&D / OREGON TECH.
Procurement and Contract Services
27500 SW Parkway Avenue
Wilsonville, OR 97070

OWNER'S REPRESENTATIVE:
CRAIG CAMPBELL, Executive Director
OMIC R&D
33701 Charles T. Parker Way

OMIC R&D
33701 Charles T. Parker Way
Scappoose, Oregon 97056
503-983-0573

OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE: AS NOTED DRAWN BY: KP CHECKED BY: AP CAD FILE: 1404-A42.DWG DATE: JAN. 28, 2020

REVISIONS

A DATE DESCRIPTION


CONTENTS:


INTERIOR ELEVATIONS & DETAILS


DETAILS

SHEET NO:

A4.2







LED WALL WASH ALONG THE WALL, TOP & BOTTOM

-CARD READER

A4.4

30"H RECEPTION DESK

-3'-10"H COUNTER

-CUTOUT METAL PNL


LED WALL WASH ALONG

-CUTOUT METAL PNL

THE WALL, TOP & BOTTOM

- REMOVE ALL DEVICES ON WALL. PATCH GPDW.

- REMOVE EXG FLR TILES & PREP FLOOR FOR LVL.



101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3

PROJECT TEAM:

CIVIL ENGINEER:
AKS ENGINEERING & FORESTRY
12965 SW Herman Road, Suite 100
Tualatin, OR 97062
P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way

Scappoose, Oregon 97056 503-983-0573 OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE: AS NOTED DRAWN BY: CHECKED BY: CAD FILE: 604A_A43-44.DWG DATE: JAN. 28, 2020


REVISIONS DATE DESCRIPTION

CONTENTS:


INTERIOR ELEVATIONS & DETAILS

SHEET NO:


A4.3



101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3



3 A4.5



ROOM NO.	ROOM NAME	FLOOR	BASE		WALL			CEILING		NOTES
	AREA	MAT		MAT	FINISH	TRIM	MAT	FINISH	TRIM	
1ST	FLOOR east									
100	ENTRY	LVT / WALK-OFF MT	WD		*			*		* SEE ELNLARGED PLAN & INT ELEVS
101	OFFICE	EXG	EXG		EXISTING			EXISTING		
102	OFFICE	11			"			11		
103	OFFICE	II.			п			ıı .		
104	OFFICE	ıı ı			"			ıı ı		
105	OFFICE	ıı .			· ·			ıı ı		
106	OFFICE	ıı ı			"			"		
107A	BRK RM	"			п			ıı ı		
		"			п			"		
107B	JANITROR		TO DUD	OPPIN			ODDIW			
108	HALL	LVT	TP-RUB	GPDW	PNT		GPDW	PNT		
109	WOMENS RR	EXG	EXG		EXISTING			EXISTING		
110	MEN'S RR	ıı			"			"		
111	DATA	n n			п			"		
112	OFFICE	CPT TILE	TP-RUB	GPDW	PNT		GPDW	PNT		
112A	STORAGE	LVT	TP-RUB	GPDW	PNT		GPDW	PNT		
113	STORAGE	LVT	TP-RUB	GPDW	PNT		GPDW	PNT		
114	RESTROOM	EXG	EXG		EXISTING			EXISTING		
115	RESTROOM	11			n n			"		
116	HALL	LVT	TP-RUB	GPDW	PNT		GPDW	PNT		
117	HALL	LVT & EXT	TP-RUB	GPDW	PNT		GPDW	PNT		
	FLOOR west	277 0. 277	11 1105	0.5			0.5	1111		
120	MEASURING	EPOXY	TP-RUB	GPDW	PNT		GPDW	PNT		
121	TESTING	EPOXY	TP-RUB	GPDW	PNT		GPDW	PNT		
122	STORAGE	EPOXY	TP-RUB	GPDW	PNT		GPDW	PNT		
122B	STORAGE	EXG	EXG		EXISTING			EXISTING		
123	COATING	EXG	EXG		EXISTING			EXISTING		
124	ELECTRICAL	ıı ı			II II			"		
125	ADA LIFT	RUBBER	TP-RUB	GPDW	PNT		GPDW	PNT		
Н	IIGH BAY									
								WHITE VAPOR		
01-1	HIGH BAY	EXG	RUB	GPDW / VB	PNT/VB			BARRIER		GPDW TO 8'-0" AFF, WHITE VB ABOVE
2ND	FLOOR - east									
	200	CPT TILE	TP-RUB	GPDW	PNT		GPDW	PNT		
200A	STORAGE	CPT TILE	TP-RUB	GPDW	PNT		GPDW	PNT		
201	OFFICE	EXG	EXG	J. 511	EXISTING		J. 511	EXISTING		
201	OFFICE	EAG "	LAG		EXISTING "			EXISTING "		
		ıı			п			п		
203	OFFICE	"			"			"		
204	OFFICE									
205	CONFERENCE	"			"			"		
206	OFFICE	CPT TILE	TP-RUB	GPDW	PNT		GPDW	PNT		
207	RESTROOM				TILE					WALL TILE WHERE CABINETS REMOVED
209	HALL	LVT & EXT	TP-RUB	GPDW	PNT		GPDW	PNT		SEE FIN PLAN & INT ELEVS
2ND F	FLOOR - west									
210A	TESTING				EXISTING					
211	OFFICE	LIN	RUB		PNT					
212	OFFICE	LIN	RUB		PNT		EXG	PNT		
213	RESTROOM	LIN	RUB	GPDW/FRP	PNT	ALM	GPDW	PNT		FRP TO 48", ALUM TRIM
214	HALL	LIN	RUB	GPDW	PNT		GPDW	PNT		
215	STORAGE	LIN	RUB	GPDW	PNT		GPDW	PNT		
216	UTIL	LIN	RUB	GPDW	PNT		GPDW	PNT		
210	JIL	LIIV	1,00	OI DVV	IIVI		O1 D11	1 111		

2 A4.5 1ST FLOOR FINISH PLAN - WEST 1ST FLOOR FINISH PLAN - EAST

1 A4.5 FINISH SCHEDULE

ST. HELENS, OREGON OF OREGO

101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3

PROJECT TEAM:

CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way Scappoose, Oregon 97056 503-983-0573

OREGON MANUFACTURING INNOVATION CENTER R & D

AS NOTED DRAWN BY:

CHECKED BY: 604A_A45-46.DWG JAN. 28, 2020

REVISIONS _____ DATE DESCRIPTION

CONTENTS:


SCALE:

CAD FILE: DATE:

FINISH SCHEDULE & FINISH FLOOR PLAN

SHEET NO:

A4.5



101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3



PROJECT TEAM:

CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director 33701 Charles T. Parker Way

Scappoose, Oregon 97056 503-983-0573 OREGON MANUFACTURING INNOVATION CENTER R & D

AS NOTED SCALE: DRAWN BY: CHECKED BY: CAD FILE: 604A_A45-46.DWG DATE: JAN. 28, 2020


REVISIONS △ DATE DESCRIPTION


CONTENTS:

2ND FLR FIN PLANS, RCP - EAST CORR.


SHEET NO:

A4.6





 $\begin{array}{c} 3 \\ \hline A5.0 \\ \end{array}$ STEEL FRAME TYPES 1/2" = 1'-0"



2	DOOR TYPES
A5.0	1/2" = 1'-0"

	01011					
	SEALANT					
	(BOTH SIDES)					
	 				DOOR NO.	ROOM
#					407.5	71 0 0 D
					100	ENTRY
	FRAME ANCHORS PER MANF SPEC				100B	ENTRY
	MANI SELO				101	OFFICE
					102	OFFICE
JAMB					103	OFFICE
IEAD SIMILA	R				104	OFFICE
OW METAL FRAM	E @ ADA LIFT				105	OFFICE
1'-0"					106	OFFICE
					107A	BRK RM
					107B 107C	JANITROR BRK RM
					107C	HALL
					108B	HALL
					109	WOMENS RR
					110	MEN'S RR
DOOR HARD	WARE SCHEDULE				111	DATA
	OTOPERANDO ELECTRICAL POOLO		0.110		112	OFFICE
GROUP #1 - NO	- STOREROOMS, ELECTRICAL ROOMS, TYPE	FINISH	JMS <u>MANF.</u>		112B	STORAGE
3 EA	BUTTS FBB168 4.5 X 4.5	652	STANLEY		113	STORAGE
1 EA 1 EA	STOREROOM LOCK ND80PD RHO WALLSTOP WS406/407CCV	626 630	SCHLAGE IVES		113B	ELEV. CONTR. RESTROOM
1 EA	OVERHEAD STOP 904S	630	GLYNN JOHNSON		115	RESTROOM
2 EA	SILENCER SR64	GRAY	IVES		116A	HALL
CROUP #2.	- GANG RESTROOMS				116B	HALL
	TYPE	FINISH	MANF.		1ST F	LOOR west
3 EA	BUTTS FBB168 4.5 X 4.5				121	TESTING
1 EA 1 EA	PUSH PLATE 8200 4 X 16 PULL PLATE 8305-0 4 X 16	630 630	IVES IVES		122A	STORAGE
	CLOSER 4011 REG	ALUM	LCN		122B	LIFT CONTR.
1 EA	WALLSTOP WS407CCV	630	IVES		123A	COATING
1 EA 3 EA	KICKPLATE 8400 10X2LDW SILENCER SR64	630 GRAY	IVES IVES		123B 124A	COATING
					124A 124B	COATING
	- SINGLE RESTROOMS TYPE	FINICLI	MANF.		125	ELECTRICAL
	BUTTS_FBB168 4.5 X 4.5					
{1 EA	CS210 - LATCH & DEADBOLT	626	<u> </u>			
1 EA	ADA COMPLIANT – INTERCONNECTED CLOSER 4011	ALUM	LCN		126	ADA LIFT
1 EA	WALLSTOP WS407CCV	630	IVES			GH BAY
1 EA	KICKPLATE 8400 10X2LDW	630	IVES		01-1	
1 SET	GASKET PS074	BLK	STEELCRAFT		01-2	
GROUP #4	, - PRIVATE OFFICES / ROOMS WITH A	ACCESS CON	ITROL *#1		01-4	
NO 7 FA	TYPE				01-5	
3 EA 1 EA	BUTTS FBB168 4.5 X 4.5 LATCH— ELECTRONIC NDE80PE	652	STANLEY) STANLEY)		01-6	
1 EA	CLOSER 4111 EDA	ALUM	Len		01-A	
2 EA	WALLSTOP WS406/407CCV	630	IVES		01-B	
3 EA	SILENCER SR64	GRAY	IVES		01-C	
GROUP #5	- PRIVATE OFFICES / ROOMS (WITH	OUT ACCES	S CONTROL)		01-D 01-E	
NO	TYPE	FINISH	MANF.		01-E	
3 EA 1 EA	BUTTS FBB168 4.5 X 4.5 LATCH ND50PD	652 626	STANLEY SCHLAGE			LOOR - east
1 EA	CLOSER 4111 EDA	ALUM	LCN		200	MEETING
2 EA	WALLSTOP WS406/407CCV	630	IVES		200A	STORAGE
3 EA	SILENCER SR64	GRAY	IVES		200B	EGRESS
GROUP #6	- MEETING ROOM (WITHOUT ACCESS	CONTROL)			201	OFFICE
NO NO	TYPE	FINISH	MANF.		202	OFFICE
1 EA 1 EA	PUSH PLATE 8200 4 X 16 PULL PLATE 8305-0 4 X 16	630 630	IVES VES		203	OFFICE
> 6 EA	BUTTS FBB168 4.5 X 4.5	652	STANLEY		204	OFFICE
2 EA	CLOSER 4111 EDA	ALUM	LCN		205A 205B	CONFERENCE
2 EA 2 EA	WALLSTOP WS406/407CCV SILENCER SR64	630 GRAY	IVES)		206	OFFICE
(4 LA	SILENCER SRO4	GNAT	IVES			207
(*HARDWARE					2ND F	LOOR - west
	: 25 ELECTRONIC ACCESS CONTROL I ONTROL SYSTEM.	LATCHES ST.	ANLEY-NDE80 LATCHES		0404	TEOTINO
	NDE80 LATCHES AT AT EXISTING [$\langle \langle$	210A	TESTING
	ND 125, ALL OTHER ROOMS WITH ACINED BY OWNER.	LUESS CONT	KUL SHALL BE	$\langle \rangle$	210B	TESTING
	TING DOORS 100A AND 107A PROVID			\ \	211	OFFICE
/ ASSA	DNIC/MAGNETIC LOCKS AND ADA AUTO —ABLOY POWERMATIC 6300 SERIES, O				212	OFFICE
/	FROM DOOR 107A B 2008 DROVIDE VON DURRIN 33/3	EVIT DE	//CE AND DIT/DIT	$\int \int$	213	RESTROOM
	R 200B PROVIDE VON DUPRIN 33/3: DNIC MONITORING KIT.	om exii De,	VIOL AIND KU/KM			
5. AT DOO	R 113B PROVIDE LCN 4111 EDA CLO	OSER ^		>	214A	STAIR
					214B	LIFT
					215	STORAGE

DOOR NO.	ROOM	RATING			DOOR				FRAME			CA	SING		SIGN	NOTES
	1.30111	(MIN)	MAT	TYPE	FIN	HEIGHT	WIDTH	MAT	TYPE	FIN	PUSH SIDE	FIN	PULL SIDE	FIN	TYPE	
1ST	FLOOR east	/	LVIIVI		r 11 V		***************************************	1417.7.1	=	1.011	. JOIT OIDL	i 11 V	. JLL SIDL	1 II V		
100	ENTRY				EXISTING											
100B	ENTRY	0	WD	D2	CLR	7'6"	3'6"	STL	F1	PNT					R1	
101	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F2	PNT					R2	
102	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R2	
103	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R2	
104	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R2	
105	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R2	
106	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F2	PNT					R2	
107A	BRK RM	U	VVD	D3	EXISTING	0.0	30	- SIL	Г	FINI					NZ	
		0	WD	Da		CIOII	21011	CTI	F4	DNT					D4	
107B	JANITROR	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
107C	BRK RM	0	WD		NO DOOR	6'8"	3'0"	STL	F2	PNT					R1	
108A	HALL				NO DOOR			STL	F1	PNT						
108B	HALL				EXISTING										R1	-
109	WOMENS RR	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
110	MEN'S RR	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
111	DATA	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
112	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R2	
112B	STORAGE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
113	STORAGE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
113B	ELEV. CONTR.	60	WD	D3	CLR	6'8"	3'6"	STL	F1						R1	
114	RESTROOM	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
115	RESTROOM	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
116A	HALL				NO DOOR	6'8"	3'0"	STL	F1	PNT						
116B	HALL				EXISTING										R1	
1ST	FLOOR west															
121	TESTING				EXISTING										R1	
122A	STORAGE				EXISTING										R1	
122B	LIFT CONTR.		WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
123A	COATING				EXISTING										R1	
123B	COATING				EXISTING										R1	
124A	COATING				EXISTING										R1	
124B	COATING				EXISTING										R1	
125	ELECTRICAL				EXISTING										R1	
120					2/4011110						VERIFY				111	
											FRAME WITH					
126	ADA LIFT	60	45	D1	CLR	6'8"	3'0"	STL	F1*	PNT	LIFT INSTALLER				R1	
	IIGH BAY				J = 11											
01-1		0			EXISTING											
01-2		0			EXISTING											
01-3		0			EXISTING											
01-3		0			EXISTING											
01-5		0			EXISTING											
01-6		0	0.71	011	EXISTING	4.41	401	O.T.	011							
01-A		0	STL	OH	PDT	14'	16'	STL	OH							
01-B		0	STL	ОН	PDT	14'	16'	STL	OH							
01-C		0	STL	OH	PDT	14'	16'	STL	OH							
01-D		0	STL	ОН	PDT	14'	16'	STL	OH							
01-E		0	STL	ОН	PDT	14'	16'	STL	ОН							
01-F		0	STL	ОН	PDT	14'	16'	STL	ОН							
	FLOOR - east															
200	MEETING	0	WD	D2	CLR	6'8"	(2) - 3'0"	STL	F1	PNT					R1	
200A	STORAGE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
200B	EGRESS				EXISTING										EXIT	
201	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R2	
202	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R2	
203	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R2	
204	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F2	PNT					R2	_
205A	CONFERENCE	0	WD	D2	CLR	6'8"	3'0"	STL	F1	PNT					R1	
205B	CONFERENCE	0	WD	D2	CLR	6'8"	3'0"	STL	F1	PNT					R1	
206	OFFICE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R2	
-	207	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
2ND I	FLOOR - west		1		_ <u>-</u>			-·-		,						
210A	TESTING	0	WD	D4	CLR	6'8"	3'0"	STL	F1	PNT					R1	
0400	TEOTINO			EXISTING											D4	
210B	TESTING		1475	OVERHEAD D4	01.5	CIO!!	010"	OT!	F.,	DATE					R1	
211	OFFICE	0	WD	D4	CLR	6'8"	3'0"	STL	F1	PNT					R2	
212	OFFICE	0	WD	D4	CLR	6'8"	3'0"	STL	F1	PNT					R2	
213	RESTROOM	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
									_	_					_	
214A	STAIR			NO DOOR		6'8"	3'0"	STL	F1	PNT	\/EDIE\/				R1	
											VERIFY FRAME WITH					
				_					_	_	LIFT				_	
214B	LIFT	60	WD	D1	CLR	6'8"	3'0"	STL	F1*	PNT	INSTALLER				R1	
215	STORAGE	0	WD	D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	
216	UTIL	0		D3	CLR	6'8"	3'0"	STL	F1	PNT					R1	t contract to the contract to

101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3



PROJECT TEAM:

CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director OMIC R&D 33701 Charles T. Parker Way Scappoose, Oregon 97056 503-983-0573

OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE:

DRAWN BY:

CAD FILE:

DATE:

CHECKED BY:

REVISIONS

AS NOTED

604A_A50.DWG

DATE DESCRIPTION 1 04/15/2020 FOR BLDG OFF REV


CONTENTS:

DOOR TYPES & SCHEDULE


SHEET NO:

FOR PERMIT


A5.0







_					
	PTN TYPE	FRAME	WALL MAT	FIRE RATING	STC RATING
	1A>	2x4	1/2" GPDW, BOTH SIDES	NONE	34
	√1B>	2x4	5/8" GPDW, BOTH SIDES	1 HR (UL DES U305)	36
	(1C)	2x4	(2) LAYERS 5/8" GPDW, BOTH SIDES	2 HR (UL DES 301)	38



PTN TYPE	FRAME	WALL MAT	FIRE RATING	STC RATING
ŹA>	2x6	1/2" GPDW BOTH SIDES	NONE	35
v				
<u>2</u> B	2x6	5/8" GPDW BOTH SIDES	1 HR (UL DES U305)	38
2C>	2x6	(2) LAYERS 5/8" GPDW, BOTH SIDES	2 HR (UL DES 301)	40

——JT OR EXTEND WALL TO

UNDERSIDE OF DECK

CEILING PER SCHEDULE

INSUALTION (SAB)

SEE TABLE BEL

FF SEE SCHED

FLR DECK

FIRE RATING


NONE

SOUND ATTENUATION BATT

STC RATING

DECK ABOVE ----

2x WD BLKG AS REQD—



				,
PTN TYPE	FRAME	WALL MAT	FIRE RATING	STC RATING
₹3A	2x4 OR 2x6	1/2" GPDW, ONE SIDE AND 1/2" OSB AND 1/2" GBDW ONE SIDE	NONE	*

<u>SECTION</u> <u>PLAN</u> PTN TYPE | FRAME WALL MAT 1/2" GPDW, ONE SIDE AND 1/2" OSB AND 1/2" GBDW ONE SIDE DBL WALL 1"GAP * NO PUBLISHED RESEARCH

DOUBLE 2x4 WD FR

@ 16" O.C

STAGGERED

GENERAL WALL & PARTITION NOTES:

* NO PUBLISHED RESEARCH


WHERE ASSEMBLY IS RATED PROVIDE FIRECORE TYPE "X" OR TYPE "C" GYPSUMBOARD

WERE ASSEMBLY IS RATED PROVIDE FIRE SEALANT AS REQUIRED TO MEET FIRE RESISTANCE RATING AND AS INDICATED IN UL ASSEMBLY

WHERE FIRE RATED ASSEMBLY IS PENETRATED PROVIDE THROUGH-PENETRATION FIRE STOP SYSTEM THAT MEETS OR EXCEEDS RATING OF ASSEMBLY PENETRATED. SEE FIRESTOPPING SCHEDULE FOR TYPICAL PENETRATIONS, FOR ATYPICAL PENETRATIONS PROVIDE AN ASSEMBLY RATED BY A TESTING AGENCY ACCEPTABLE TO AUTHORITIES HAVING JURISDICTION.


WHERE WALL ASSEMBLY IS LOCATED IN "WET" LOCATION: RESTROOM, KITCHEN, JANITOR CLOSET, OR OTHER SUCH LOCATION PROVIDE "BLUE BOARD" - WATER AND MOLD RESISTANT GYPSUM BOARD OF THICKNESS AND FIRE RATING INDICATED.





8 A3.3 SIM

101 ST HELENS ST ST HELENS, OR 97051 T: 503 366 3050 F: 503 3



PROJECT TEAM:

CIVIL ENGINEER: AKS ENGINEERING & FORESTRY 12965 SW Herman Road, Suite 100 Tualatin, OR 97062 P: 503.563.6151 F: 503.563.6152

STRUCTURAL ENGINEER: PETERSON STRUCTURAL ENGINEERS 9400 SW Barnes Road, Suite 100 Portland, OR 97225 P. 503.292.1635

MEP ENGINEER: FLUENT ENGINEERING INC. 2110 State Street Salem, Oregon 97301 P. 503-447-5030

OWNER: OMIC R&D / OREGON TECH. Procurement and Contract Services 27500 SW Parkway Avenue Wilsonville, OR 97070

OWNER'S REPRESENTATIVE: CRAIG CAMPBELL, Executive Director 33701 Charles T. Parker Way Scappoose, Oregon 97056 503-983-0573

OREGON MANUFACTURING INNOVATION CENTER R & D

SCALE: AS NOTED DRAWN BY: CHECKED BY: CAD FILE: 604A_A50 DATE:

REVISIONS DATE DESCRIPTION 1 03/26/2020 FOR BLDG OFF REV

CONTENTS:

PTN & WIN TYPES & DETAILS

SHEET NO: